AC326A

AS-Interface dual sensor for pneumatic valve actuators

DUAL SENSOR T5 2SI 1DO T/3G



Product characteristics		
Sensing range	[mm]	4
Dimensions	[mm]	55 x 60 x 35
Electrical data		
Operating voltage	[V]	26.5...31.6 DC
Current consumption	[mA]	< 160
Protection class		III
Detection zone		
Sensing range	[mm]	4

AC326A

AS-Interface dual sensor for pneumatic valve actuators

DUAL SENSOR T5 2SI 1DO T/3G

Operating distance target puck	[mm]	74	
Operating conditions			
Ambient temperature	[°C]	-10...50	
Protection		IP 67	
Tests / approvals			
ATEX marking		II 3G Ex nA IIC T6 Gc X	
Note on ATEX marking		only in conjunction with the impact protection housing	
EMC		EN 50295	
MTTF	[years]	310	
AS-i classification			
AS-i version		2.1	
Extended addressing mode		yes	
AS-i I/O configuration	[hex]	7	
AS-i ID code	[hex]	A.E	
Mechanical data			
Weight	[g]	766.5	
Dimensions	[mm]	55 x 60 x 35	
Materials		housing: PBT orange; cover: PC black; Impact protection housing: stainless steel	
Displays / operating elements			
Display		operation	1 x LED, green
		function	1 x LED, yellow
Accessories			
Items supplied		Impact protection housing	
		Mounting plate: 1	
		socket head screws: 2 x M5 x 35	
Remarks			
Pack quantity		1 pcs.	

Electrical connection - plug

Connector: 1 x M12; coding: A; Moulded body: stainless steel

Elektrischer Anschluss	
1	AS-i+
3	AS-i -

AC326A

AS-Interface dual sensor for pneumatic valve actuators

DUAL SENSOR T5 2SI 1DO T/3G

Electrical connection - socket

Connector: 1 x M12; coding: A; Moulded body: stainless steel



Connection

Ausgänge

3	external voltage -
4	switching output +
1, 2, 5	nicht belegt