

ISO-Kalibrierung Temp. N-Pkt

ifm electronic 

Auftragsnummer:
job no.:
Referenzgerät:
reference unit:
Prüfnormal, Temperatur:
testing device, temperature:
Serien-Nr.:
serial no.:
PTB-Zertifikat:
PTB certificate:
Umgebungstemperatur:
ambient temperature:

Left Hand Stressor rate	Left Hand Strain rate	Stress/Strain Ratio
75	75	1.00
100	100	1.00
125	125	1.00
150	150	1.00

[illegible]

Microsoft Teams for Office 365 users automatically installs and is then automatically getting updates. No updates for non-privileged users will be without updates.

Site name	Location	Year
Site 1	Location 1	Year 1
Site 2	Location 2	Year 2
Site 3	Location 3	Year 3
Site 4	Location 4	Year 4
Site 5	Location 5	Year 5
Site 6	Location 6	Year 6
Site 7	Location 7	Year 7
Site 8	Location 8	Year 8
Site 9	Location 9	Year 9
Site 10	Location 10	Year 10
Site 11	Location 11	Year 11
Site 12	Location 12	Year 12
Site 13	Location 13	Year 13
Site 14	Location 14	Year 14
Site 15	Location 15	Year 15
Site 16	Location 16	Year 16
Site 17	Location 17	Year 17
Site 18	Location 18	Year 18
Site 19	Location 19	Year 19
Site 20	Location 20	Year 20
Site 21	Location 21	Year 21
Site 22	Location 22	Year 22
Site 23	Location 23	Year 23
Site 24	Location 24	Year 24
Site 25	Location 25	Year 25
Site 26	Location 26	Year 26
Site 27	Location 27	Year 27
Site 28	Location 28	Year 28
Site 29	Location 29	Year 29
Site 30	Location 30	Year 30
Site 31	Location 31	Year 31
Site 32	Location 32	Year 32
Site 33	Location 33	Year 33
Site 34	Location 34	Year 34
Site 35	Location 35	Year 35
Site 36	Location 36	Year 36
Site 37	Location 37	Year 37
Site 38	Location 38	Year 38
Site 39	Location 39	Year 39
Site 40	Location 40	Year 40
Site 41	Location 41	Year 41
Site 42	Location 42	Year 42
Site 43	Location 43	Year 43
Site 44	Location 44	Year 44
Site 45	Location 45	Year 45
Site 46	Location 46	Year 46
Site 47	Location 47	Year 47
Site 48	Location 48	Year 48
Site 49	Location 49	Year 49
Site 50	Location 50	Year 50
Site 51	Location 51	Year 51
Site 52	Location 52	Year 52
Site 53	Location 53	Year 53
Site 54	Location 54	Year 54
Site 55	Location 55	Year 55
Site 56	Location 56	Year 56
Site 57	Location 57	Year 57
Site 58	Location 58	Year 58
Site 59	Location 59	Year 59
Site 60	Location 60	Year 60
Site 61	Location 61	Year 61
Site 62	Location 62	Year 62
Site 63	Location 63	Year 63
Site 64	Location 64	Year 64
Site 65	Location 65	Year 65
Site 66	Location 66	Year 66
Site 67	Location 67	Year 67
Site 68	Location 68	Year 68
Site 69	Location 69	Year 69
Site 70	Location 70	Year 70
Site 71	Location 71	Year 71
Site 72	Location 72	Year 72
Site 73	Location 73	Year 73
Site 74	Location 74	Year 74
Site 75	Location 75	Year 75
Site 76	Location 76	Year 76
Site 77	Location 77	Year 77
Site 78	Location 78	Year 78
Site 79	Location 79	Year 79
Site 80	Location 80	Year 80
Site 81	Location 81	Year 81
Site 82	Location 82	Year 82
Site 83	Location 83	Year 83
Site 84	Location 84	Year 84
Site 85	Location 85	Year 85
Site 86	Location 86	Year 86
Site 87	Location 87	Year 87
Site 88	Location 88	Year 88
Site 89	Location 89	Year 89
Site 90	Location 90	Year 90
Site 91	Location 91	Year 91
Site 92	Location 92	Year 92
Site 93	Location 93	Year 93
Site 94	Location 94	Year 94
Site 95	Location 95	Year 95
Site 96	Location 96	Year 96
Site 97	Location 97	Year 97
Site 98	Location 98	Year 98
Site 99	Location 99	Year 99
Site 100	Location 100	Year 100

Poids	[g]	19,171
-------	-----	--------

Remarques	Le certificat de calibrage ISO n'est pas reconnu selon l'EA MLA
-----------	---

Remarques

Le certificat de calibrage ISO n'est pas reconnu selon l'EA MLA (Multilateral Agreement) et est donc considéré comme non traçable.
Le certificat de calibrage doit être commandé en combinaison avec un capteur.
La livraison de l'appareil correspondant comprend le certificat de calibrage.
Le certificat de calibrage est bilingue (allemand/anglais)
Des commandes ultérieures sont seulement possibles si l'appareil est dans un état propre lors du retour.
Dans la version internet de la fiche technique un certificat modèle est disponible sous l'onglet "Téléchargement".
4 points de mesure au maximum à sélectionner selon les exigences du client
Plage de température -20°C...150°C