AC2026

AS-Interface illuminated pushbutton module

EMS Module 2BI 2LO

Article no longer available - archive entry

Alternative articles: AC2086

When selecting an alternative article and accessories please note that technical data may differ!



1 panel for labelling
2 pushbutton / LED
3 pushbutton / LED

Application		
Application		field installation
Electrical data		
Operating voltage	[V]	26.5...31.6 DC
Max. current consumption from AS-i	[mA]	55
Inputs		
Sensor supply of the inputs		AS-i
Operating conditions		
Ambient temperature	[°C]	-25...60
Protection		IP 67
Tests / approvals		
EMC		EN 50295
AS-i classification		
AS-i version		2.1
Extended addressing mode		no
AS-i master profile		M2; M3; M4

AC2026

AS-Interface illuminated pushbutton module

EMS Module 2BI 2LO

AS-i profile		S-3.F.F				
AS-i I/O configuration	[hex]	3				
AS-i ID code	[hex]	F.F				
AS-i certificate		04801				
Assignment of the data bits		data bit	D0	D1	D2	D3
		pushbutton	2	1	-	-
		LED	-	-	2	1
Mechanical data						
Weight	[g]	100.6				
Type of mounting		AS-i interface to FC and SC lower parts				
Materials		PBT				
Displays / operating elements						
Display		pushbutton	2 x LED, white			
Accessories						
Items supplied		cover support: 2				
		colour inserts: 2, red				
		2, green				
		2, yellow				
		2, blue				
		2, white				
Remarks						
Remarks		The pushbuttons (EAO type 84) provide protection against accidental contact.				
		Housing and pushbuttons can be labelled.				
Pack quantity		1 pcs.				
Electrical connection						
contact pins to module lower part, FK / PG:						