IN5317

Inductive dual sensor for valve actuators

IND3004DBPKG/T2

Article no longer available - archive entry

Alternative articles: IN5334

When selecting an alternative article and accessories please note that technical data may differ!



1 field connection

Product characteristics		
Electrical design		PNP
Sensing range	[mm]	4
Housing		rectangular
Dimensions	[mm]	40 x 26 x 60
Application		
Application		for actuators using standard ISO 5211 (VDI/VDE) mounting
Electrical data		
Operating voltage	[V]	10...36 DC
Current consumption	[mA]	20; (24 V)
Reverse polarity protection		no
Outputs		
Electrical design		PNP
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	250
Switching frequency DC	[Hz]	1300
Short-circuit protection		no
Overload protection		no

IN5317

Inductive dual sensor for valve actuators

IND3004DBPKG/T2

Detection zone			
Sensing range	[mm]		4
Operating conditions			
Ambient temperature	[°C]		-25...80
Protection			IP 67
Mechanical data			
Housing			rectangular
Mounting			non-flush mountable
Dimensions	[mm]		40 x 26 x 60
Materials			PBT; PC
Displays / operating elements			
Display		switching status	2 x LED, yellow
Remarks			
Pack quantity			1 pcs.
Electrical connection			
Connector: 1 x Rd24			
Connector: 1 x M12			