

AC1006



AS-Interface PROFIBUS DP gateway with PLC

Contr 2MSTR 1RS232C 1DP


Article no longer available - archive entry

Alternative articles: AC1028

When selecting an alternative article and accessories please note that technical data may differ!

Replacement units for Krones systems should be obtained directly from the company Krones.

This unit is not directly compatible.



- 1 serial interface RS232C
- 2 PROFIBUS DP interface



Application

Application use as minicontroller and gateway

Electrical data

Operating voltage [V]	22...30 DC; (24 DC; to PELV)
Insulation rating [V]	500
Max. current consumption from AS-i [mA]	80
Max. power consumption [VA]	10
Electrical separation	yes

Outputs

Electrical design AS-i

Interfaces

Communication interface RS232

AC1006



AS-Interface PROFIBUS DP gateway with PLC

Contr 2MSTR 1RS232C 1DP

RS232		
Number of R232 interfaces	1	
Transmission rate	4800...62400 Baud	
Connector type	SUB-D	
Usage type	programming	
Operating conditions		
Ambient temperature [°C]	0...60	
Storage temperature [°C]	-20...70	
Max. relative air humidity [%]	95	
Protection	IP 20	
AS-i classification		
AS-i profile	M1	
AS-i certificate	22501	
Mechanical data		
Housing	housing for DIN rail mounting	
Materials	aluminium	
Displays / operating elements		
Display	operation	2 x LED, red
		2 x LED, green
		2 x LED, yellow
Remarks		
Remarks	Replacement units for Krones systems should be obtained directly from the company Krones. This unit is not directly compatible.	
Notes	Replacement units for Krones systems should be obtained directly from the company Krones.; This unit is not directly compatible.	
Pack quantity	1 pcs.	

AC1006



AS-Interface PROFIBUS DP gateway with PLC

Contr 2MSTR 1RS232C 1DP

Electrical connection

screw terminals: 7 x

Connection

7	AS-i 2+
6	AS-i 2-
5	+ 24 V
4	0 V
3	AS-i 1+
2	AS-i 1-
1	PE