




Through-beam sensor receiver

OJE-FPKG/SO/AS



1 pushbutton



Product characteristics		
Type of light		red light
Housing		rectangular
Application		
Function principle		Through-beam sensor
Electrical data		
Operating voltage	[V]	10...30 DC
Current consumption	[mA]	< 12
Protection class		III
Reverse polarity protection		yes
Type of light		red light
Wave length	[nm]	660
Outputs		
Electrical design		PNP
Output function		light-on/dark-on mode; (programmable)
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	200



## Through-beam sensor receiver

OJE-FPKG/SO/AS

Switching frequency DC	[Hz]	1200
Short-circuit protection		yes
Type of short-circuit protection		pulsed
Overload protection		yes

## Detection zone

Transmitter / receiver		receiver
Range	[m]	< 10
Range adjustable		yes

## Operating conditions

Ambient temperature	[°C]	-25...60
Protection		IP 67

## Tests / approvals

EMC		EN 60947-5-2
MTTF	[years]	952

## Mechanical data

Weight	[g]	26.9
Housing		rectangular
Dimensions	[mm]	35 x 11 x 24
Materials		housing: ABS; LED window: SEPS; pushbutton: SEPS
Lens material		glass
Lens alignment		side lens

## Displays / operating elements

Display	switching status	1 x LED, yellow
	operation	1 x LED, green
	function	1 x LED, red
Electronic lock		yes

## Accessories

Items supplied		screws: 2
		spring washers: 2
		Nuts: 2

## Remarks

Remarks		operating voltage "supply class 2" according to cULus
Pack quantity		1 pcs.

## Electrical connection


Connector: 1 x M8; coding: A



## Through-beam sensor receiver

OJE-FPKG/SO/AS

## Connection



2 Teach

## Diagrams and graphs

excess gain graph

