RN6040

Absolute singleturn encoder with solid shaft

RN-0256-G24/L6A

Article no longer available - archive entry

Alternative articles: RN6012

When selecting an alternative article and accessories please note that technical data may differ!



1 M4 Depth 5 mm

Product characteristics		
Resolution		256 resolution
Communication interface		parallel
Shaft design		solid shaft
Shaft diameter	[mm]	6
Electrical data		
Operating voltage	[V]	10...30 DC
Current consumption	[mA]	< 150
Max. revolution electrical	[U/min]	6000
Outputs		
Electrical design		HTL
Max. current load per output	[mA]	20
Type of short-circuit protection		< 60 s
Code		Gray code; (increasing code values when turned clockwise (seen on the shaft))
Measuring/setting range		
Resolution		256 resolution
Interfaces		
Communication interface		parallel

RN6040

Absolute singleturn encoder with solid shaft

RN-0256-G24/L6A

Operating conditions		
Ambient temperature	[°C]	-20...70
Storage temperature	[°C]	-30...100
Max. relative air humidity	[%]	98
Protection		IP 65

Tests / approvals	
Shock resistance	100 g (6 ms)
Vibration resistance	10 g (55...2000 Hz)

Mechanical data		
Dimensions	[mm]	Ø 58 / L = 76
Materials		aluminium
Max. revolution, mechanical	[U/min]	10000
Max. starting torque	[Nm]	1
Reference temperature torque	[°C]	20
Shaft design		solid shaft
Shaft diameter	[mm]	6
Shaft material		steel (1.4104)
Max. shaft load axial (at the shaft end)	[N]	10
Max. shaft load radial (at the shaft end)	[N]	20

Electrical connection

Cable: 6 m, PUR; Maximum cable length: 100 m; axial

brown	10...30V
yellow/brown	10...30V sensor
white	0V
white/yellow	0V sensor
green	release A inverted 5...30V
yellow	release B inverted 5...30V
white/grey	bit 8 (MSB) inverted
brown/green	bit 8 (MSB)
white/green	bit 7
red/blue	bit 6
grey/pink	bit 5
lilac	bit 4
black	bit 3
red	bit 2
blue	bit 1
Screen	housing

RN6040

Absolute singleturn encoder with solid shaft

RN-0256-G24/L6A

Diagrams and graphs

Pulse diagram



release A inverted

release B inverted

tracks 3...10

tracks 1...2