


Flow monitor

SCR12ABAFPKG/US-100/48VDC

Article no longer available - archive entry

Alternative articles: SI0555

When selecting an alternative article and accessories please note that technical data may differ!



Product characteristics

Number of inputs and outputs	Number of digital outputs: 1
Process connection	G 1/2 external thread

Application

Media	Liquids
Medium temperature [°C]	-25...80
Pressure rating [bar]	30

Electrical data

Operating voltage tolerance [%]	> -10
Operating voltage [V]	48 DC
Current consumption [mA]	< 45
Reverse polarity protection	yes
Power-on delay time [s]	< 20

Inputs / outputs

Number of inputs and outputs	Number of digital outputs: 1
------------------------------	------------------------------

Outputs

Total number of outputs	1
Output signal	switching signal
Electrical design	PNP

ST0510



Flow monitor

SCR12ABAFPKG/US-100/48VDC

Number of digital outputs	1
Output function	normally open / normally closed; (parameterisable)
Max. voltage drop switching output DC [V]	2.5
Permanent current rating of switching output DC [mA]	400
Short-circuit protection	yes
Type of short-circuit protection	pulsed
Overload protection	yes

Measuring/setting range	
Setting range [cm/s]	3...300
Greatest sensitivity [cm/s]	3...60

Accuracy / deviations	
Temperature gradient [K/min]	15

Response times	
Response time [s]	1...10

Software / programming	
Adjustment of the switch point	potentiometer

Operating conditions	
Ambient temperature [°C]	-20...80
Protection	IP 67

Mechanical data	
Materials	PBT-GF20
Materials (wetted parts)	stainless steel (303/1.4305)
Process connection	G 1/2 external thread

Displays / operating elements		
Display	function	11 x LED

Remarks	
Pack quantity	1 pcs.

Electrical connection

Connector: 1 x M12; coding: A



ST0510



Flow monitor

SCR12ABAFPKG/US-100/48VDC

Connection

