




Continuous level sensor

LK0728A-A-00KMPKG/US

Article no longer available - archive entry

Alternative articles: LK3124

When selecting an alternative article and accessories please note that technical data may differ!



- 1 7-segment LED display
- 2 programming buttons
- 3 housing connection with cable lug for cable 1.5...2.5 mm²



Product characteristics

Number of inputs and outputs	Number of digital outputs: 1; Number of analogue outputs: 1
Probe length L [mm]	728

Application

Special feature	Gold-plated contacts
Media	hydrous coolants; mineral oils (dielectric constant < 3); water; media similar to water
Dielectric constant of the medium	> 2
Cannot be used for	media with separation layers (oil / water; oil / metal layer); acids and alkalis
Medium temperature [°C]	0...65; (medium temperature for oils; medium temperature for coolant emulsions, water and hydrous media)
Tank pressure [bar]	0.5; (when mounting with mounting accessories: E43001 - E43007, E43019)

Electrical data

Operating voltage [V]	18...30 DC
Current consumption [mA]	< 80
Protection class	III



Continuous level sensor

LK0728A-A-00KMPKG/US

Reverse polarity protection	yes
Power-on delay time [s]	3
Measuring principle	capacitive

Inputs / outputs

Number of inputs and outputs	Number of digital outputs: 1; Number of analogue outputs: 1
------------------------------	---

Outputs

Total number of outputs	2
Output signal	switching signal; analogue signal
Electrical design	PNP
Number of digital outputs	1
Output function	normally open / normally closed; (parameterisable)
Max. voltage drop switching output DC [V]	2.5
Permanent current rating of switching output DC [mA]	200
Number of analogue outputs	1
Analogue current output [mA]	4...20
Max. load [Ω]	500
Analogue voltage output [V]	0...10
Min. load resistance [Ω]	2000
Short-circuit protection	yes
Type of short-circuit protection	pulsed
Overload protection	yes

Measuring/setting range

Probe length L [mm]	728
Active range A [mm]	585
Inactive range I1 / I2 [mm]	102 / 40
Setting range	
Set point SP [mm]	60...610
Reset point rP [mm]	50...600
In steps of [mm]	10
Hysteresis [mm]	10

Accuracy / deviations

Measuring error [% of the final value]	± 5
Repeatability	± 2

Software / programming

Adjustment of the switch point	programming button
--------------------------------	--------------------

Operating conditions

Ambient temperature [°C]	0...60
Storage temperature [°C]	-25...80
Protection	IP 67

LK3024



Continuous level sensor

LK0728A-A-00KMPKG/US

Tests / approvals		
EMC	EN 61000-4-2 ESD	4 kV CD / 8 kV AD
	EN 61000-4-3 HF radiated	10 V/m
	EN 61000-4-4 Burst	2 kV
	EN 61000-4-5 Surge	500 V / 1 kV
	EN 61000-4-6 HF conducted	10 V
Shock resistance		12 g
Vibration resistance		2.5 g

Mechanical data		
Dimensions	[mm]	Ø 16
Materials		EPDM/X; FKM; brass Optalloy-plated; NBR; PA; PBT; PC; PP
Materials (wetted parts)		PP

Displays / operating elements		
Display	switching status	LED, red
	function display	7-segment LED display
	measured values	7-segment LED display

Remarks	
Remarks	For water and hydrous media with temperatures > 35 °C install the unit into a climatic tube.
Pack quantity	1 pcs.

Electrical connection

Connector: 1 x M12; coding: A; Contacts: gold-plated



Connection

