



ISO-kalibrointitodistus virtausantureille

ISO KALIBRIERUNG SM ATM GERÄTE

Werkskalibrierschein
Factory calibration certificate

Messumformer-Typ: SM6x2x

transmitter type: SM6x2x

Serien-Nr.: 12345678

serial no.: 12345678

Messbereich: 0...1000 l/h

temperature range: 0...1000 l/h

Ausgangssignal: 4...20 mA

output: 4...20 mA

Genauigkeit: ±0.1% (FS)

accuracy: ±0.1% (FS)

Kalibrierdatum: 12.12.2022

date of calibration: 12.12.2022

Auftragsnummer: 12345678

job no.: 12345678

Referenzgerät: 12345678

reference unit: 12345678

Prüfnorm, Temperatur: DIN EN ISO 9001

testing device, temperature: DIN EN ISO 9001

Serien-Nr.: 12345678

serial no.: 12345678

PTB-Zertifikat: 12345678

PTB certificate: 12345678

Umgebungstemperatur: 20 °C

ambient temperature: 20 °C

The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards.

The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards.

The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards.

The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards.

The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards.

The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards.

The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards.

The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards.

The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards.

The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards. The calibration was performed in accordance with the requirements of the "Technical Specification" and the relevant standards.

Sovellutus	
Malli	tyypille SM6x2x, SM7x2x, SM8x2x, SM8x3x
Mekaaniset tiedot	
Paino	[g] 33,17
Huomautuksia	
Huomautuksia	Kalibrointitodistus on tilattava anturilauksen yhteydessä. K.o. anturi toimitetaan yhdessä kalibrointitodistuksen kanssa. Kalibrointitodistus toimitetaan kahdella kielellä (saksa/englanti). Uudelleenkalibrointi tai jälkitilaukset ovat mahdollisia vain, jos laite palautetaan puhtaana, ilman kiinnitettyjä lisävarusteita (toimituskunnossa) ja yhdessä täytetyn puhdistusilmoituksen kanssa. Esimerkkisertifikaatti löytyy datalehdien internet-version Downloads-välileheltä.