

Technical drawing of the LED module showing top and side views with dimensions.

Top View Dimensions:

- Overall width: 125
- Overall height: 18
- Mounting hole diameter: 11
- LED array width: 36
- LED array height: 39
- LED array pitch: 4,5
- LED array type: M12x1
- LED array label: LED

Side View Dimensions:

- Overall width: 107
- Overall height: 60
- Mounting hole diameter: 11
- LED array width: 36
- LED array height: 39
- LED array pitch: 4,5
- LED array type: M12x1
- LED array label: LED

Posebno svojstvo	bez silikona; bez halogena; Pozlaćeni kontakti
Bez silikona	da

Radni napon	[V]	10...30 DC
Zaštitna klasa		II
Maks. strujno opterećenje po modulu/utoru	[A]	4
Maks. ukupno strujno opterećenje	[A]	12

Električna izvedba	PNP
--------------------	-----

Temperatura okoline	[°C]	-15...80
Zaštita		IP 67



Razdjelna kutija

ZDO6H05DMSS0010H15

Mehanički podaci

Materijali	TPU	
Materijal ulivenog tijela	TPU	
Broj ulaza razdjelne kutije	6	
Vrsta konektora	M12	

Prikazi / radni elementi

Prikaz	Status prekapčanja	12 x LED, Žuto
	Pogon	1 x LED, Zeleno

Opaske


Količina pakiranja	1 kom.
--------------------	--------

Električni priključak

Kabel: 10 m, PUR, bez halogena; 12 x 0,5 mm² (63 x Ø 0,1 mm) + 3 x 1,0 mm² (127 x Ø 0,1 mm)

Električni priključak - utor

Poveznik: 6 x M12; kodiranje: A; Oblikovana karoserija: TPU; Kontakti: pozlaćeno; Zakretni moment pritezanja: 0,5 Nm





Razdjelna kutija

ZDO6H05DMSS0010H15

Priključak



BN =
BU =
GN =
GY =
PK =
RD =
WH =
YE =

Boje žica :
Smeđe
Plavo
Zeleno
Sivo
Ružičasto
Crveno
Bijelo
Žuto