

ZDO6H050MSS0005H07

Produk alternatif: EBC017

Fitur khusus	Bebas dari silikon; Bebas halogen; Kontak berlapis emas
Bebas dari silikon	ya

Tegangan pengoperasian	[V]	< 60 AC / < 75 DC
Kelas perlindungan		II
Beban arus maks. per modul/ slot	[A]	4
Total beban arus maks.	[A]	12

Suhu sekitar	[°C]	-15...80
Perlindungan		IP 67



Kotak splitter

ZDO6H050MSS0005H07

Data teknis	
Material	TPU
Material bodi detakan	TPU
Jumlah port kotak splitter	6
Tipe konektor	M12


Keterangan	
Jumlah paket	1 buah

Koneksi listrik

Kabel: 5 m, PUR, Bebas halogen, hitam, Ø 9 mm; 6 x 0.34 mm² (43 x Ø 0.1 mm) + 3 x 0.75 mm² (95 x Ø 0.1 mm)

Koneksi listrik - slot

Konektor: 6 x M12; pengkodean: A; Bodi cetakan: TPU; Kontak: dilapisi emas; Torsi pengencangan: 0.5 Nm



Koneksi

BN	1 (1...6)
BU	3 (1...6)
GN/YE	5 (1...6)
WH	4 (1)
GN	4 (2)
YE	4 (3)
GY	4 (4)
PK	4 (5)
RD	4 (6)

BN =	Warna core :
BU =	coklat
GN =	biru
GY =	hijau
PK =	abu-abu
RD =	merah muda
WH =	merah
YE =	putih
	kuning