

YDOAH040MSS0003H04STGH040MSS

Technical drawing of a 3-Wege-Kabelverschraubung (3-way cable gland) showing side and end views with dimensions.

Side View Dimensions:

- Top mounting thread: M12x1
- Top mounting nut height: 15
- Top mounting nut width: 14
- Mounting flange diameter: Ø4,2
- Mounting flange thickness: 17
- Mounting flange to cable entry distance: 50
- Overall length: L

End View Dimensions:

- End mounting thread: M12x1
- End mounting nut height: 15,5
- End mounting nut width: 14
- End mounting nut to cable entry distance: 36,5
- End mounting nut to cable entry distance (total): 26,5

Labels:

- A: Cable entry point
- B: Cable entry point
- C: Mounting flange

CE cUL US UK
LISTED CA

IP 65; IP 67; IP 68; IP 69K



Kabel koneksi Y

YDOAH040MSS0003H04STGH040MSS


Data teknis		
Berat	[g]	214
Material bodi detakan		TPU
Material mur		kuningan, berlapis nikel
Material penyegel		FKM
Jumlah port kotak splitter		2
Kesesuaian rantai tarik		ya
Kesesuaian rantai tarik	radius pembengkokan untuk penggunaan yang fleksibel	min. 10 x diameter kabel
	kecepatan pergerakan	maks. 3,3 m/dtk untuk panjang pergerakan horizontal 5 m dan akselerasi maks. 5 m/dtk ²
	siklus pembengkokan	> 5 Mio.
	ketegangan torsional	± 180 °/m

Keterangan	
Catatan	Lihat catatan teknis di bagian "Download"
Jumlah paket	1 buah

Koneksi listrik	
Kabel: 3 m, PUR, Bebas halogen, hitam, Ø 4.3 mm; 4 x 0.34 mm ² (42 x Ø 0.1 mm)	

Koneksi listrik - colokan	
---------------------------	--

Konektor: 1 x M12, lurus; pengkodean: A; Bodi cetakan: TPU, oranye; Penguncian: kuningan, berlapis nikel; Kontak: dilapisi emas; Torsi pengencangan: 0.6...1.5 Nm



Kabel koneksi Y

YDOAH040MSS0003H04STGH040MSS

Koneksi



Koneksi listrik - soket

Konektor: 2 x M12, bersiku; pengkodean: A; Bodi cetakan: TPU, oranye; Penguncian: kuningan, berlapis nikel; Segel: FKM; Kontak: dilapisi emas; Torsi pengencangan: 0.6...1.5 Nm



Kabel koneksi Y

YDOAH040MSS0003H04STGH040MSS

Diagram dan grafik

Derating I_{max} * 0.8 DIN EN 60512-5-2

X Suhu sekitar [°C]

Y Arus [A]