


Sensor induktif

IDC2050BBRKG/UP/0,80M/PUR/US

Produk tidak tersedia - entri arsip



Karakteristik produk

Desain kelistrikan	PNP/NPN
Fungsi output	biasanya tertutup
Jangkauan pendeteksian [mm]	50
Casing	persegi panjang
Dimensi [mm]	92 x 80 x 40

Data kelistrikan

Tegangan pengoperasian [V]	10...55 DC
Kelas perlindungan	II
Pelindung polaritas terbalik	ya


Output

Desain kelistrikan	PNP/NPN
Fungsi output	biasanya tertutup
Penurunan tegangan maks. pada output peralihan DC [V]	4.6
Arus beban minimal [mA]	4
Kebocoran arus maks. [mA]	0.6
Peringkat arus permanen dari output peralihan DC [mA]	400
Frekuensi peralihan DC [Hz]	90
Pelindung hubung singkat	ya
Tipe pelindung hubung singkat	berpulsa
Pelindung beban berlebih	ya



Sensor induktif

IDC2050BBRKG/UP/0,80M/PUR/US

Zona pendeteksian		
Jangkauan pendeteksian	[mm]	50
Jarak pengoperasian	[mm]	0...40.5; (flush mountable dengan baja ringan (ST37))
Akurasi/deviasi		
Faktor koreksi		baja: 1 / baja tahan karat: 0.7 / kuningan: 0.4 / aluminium: 0.3 / tembaga: 0.2
Histeresis	[X01]	3...20
Deviasi titik peralihan	[X01]	-15...15
Kondisi pengoperasian		
Suhu sekitar	[°C]	-25...70
Perlindungan		IP 67
Pengujian/persetujuan		
EME	EN 60947-5-2	
Data teknis		
Casing		persegi panjang
Pemasangan		flush mountable
Dimensi	[mm]	92 x 80 x 40
Material		PPE; PPE; kuningan berlapis nikel
Elemen display/pengoperasian		
Display	status peralihan	1 x LED, kuning
Aksesori		
Item dikirim		colokan penyegel: 1
Keterangan		
Jumlah paket		1 buah
Koneksi listrik - colokan		
Kabel: 0.8 m, PUR		
Konektor: 1 x M12; pengkodean: A		
		



Sensor induktif

IDC2050BBRKG/UP/0,80M/PUR/US

Koneksi

