


IIA2015-FRKG/V4A/US-100-IRF/RT





Sensor induktif

IIA2015-FRKG/V4A/US-100-IRF/RT

Jarak pengoperasian	[mm]	0...12.1
Akurasi/deviasi		
Faktor koreksi		baja: 1 / baja tahan karat: 0.7 / kuningan: 0.5 / aluminium: 0.4 / tembaga: 0.3
Histeresis	[X01]	3...15
Deviasi titik peralihan	[X01]	-10...10
Kondisi pengoperasian		
Suhu sekitar	[°C]	-25...80
Perlindungan		IP 67
Pengujian/persetujuan		
EME		EN 60947-5-2
		EN 55011
		kelas B
MTTF	[ANN]	1835
Data teknis		
Berat	[g]	150.5
Casing		tipe berulir
Pemasangan		non-flush mountable
Dimensi	[mm]	M30 x 1.5 / L = 78
Penamaan ulir		M30 x 1.5
Material		baja tahan karat (1.4571 / 316Ti); permukaan pendeteksian: PBT
Elemen display/pengoperasian		
Display	status peralihan	1 x LED, merah
Aksesori		
Item dikirim		mur pengunci: 2
Keterangan		
Jumlah paket		1 buah

Sensor induktif

IIA2015-FRKG/V4A/US-100-IRF/RT

Koneksi listrik - colokan

Konektor: 1 x M12; pengkodean: A; Kontak: dilapisi emas

