



Sensor retro-reflektif

OAP-FKOA/VRG

Produk tidak tersedia - entri arsip

Produk alternatif: OA0106
Ketika memilih produk dan aksesoris alternatif, perhatikan bahwa data teknis mungkin berbeda!

The technical drawing shows two views of the OA0116 sensor. The front view (left) shows a rectangular unit with a width of 30 mm and a height of 56 mm. It features two LED indicators, one at the top and one at the bottom. The side view (right) shows a depth of 70 mm and a height of 90 mm. It includes three mounting holes on the side, with dimensions 22 mm, 5.5 mm, and 5 mm. A label '1' points to a switch/potentiometer located below the top receiver lens and the bottom transmitter lens.

1 switch pemilih dan potensiometer di bawah penutup receiver di lensa atas
transmitter di lensa bawah

Karakteristik produk		
Tipe cahaya		cahaya merah
Casing		persegi panjang
Aplikasi		
Fitur khusus		filter polarisasi
Prinsip fungsi		Sensor retro-reflektif
Data kelistrikan		
Frekuensi AC	[Hz]	47...63
Tegangan pengoperasian	[V]	20...250 AC/DC
Konsumsi daya maks.	[VA]	2
Kelas perlindungan		II
Tipe cahaya		cahaya merah
Panjang gelombang	[nm]	660
Output		
Desain kelistrikan		relai
Fungsi output		mode light-on/dark-on; (dapat ditentukan parameternya)
Peringkat kontak		250 V AC / 3 A / 360 VA, 125 V DC / 3 A / 30 W



Sensor retro-reflektif

OAP-FKOA/VRG

Frekuensi peralihan AC	[Hz]	10
Frekuensi peralihan DC	[Hz]	10
Pelindung hubung singkat		tidak
Pelindung beban berlebih		tidak

Zona pendeteksian

Jarak jangkauan	[m]	< 8
Jangkauan yang dapat disesuaikan		ya
Tersedia filter polarisasi		ya

Kondisi pengoperasian

Suhu sekitar	[°C]	-25...60
Perlindungan		IP 65

Pengujian/persetujuan

EME	EN 60947-5-2	
	EN 55011	kelas B

Data teknis

Casing		persegi panjang
Dimensi	[mm]	90 x 30 x 70
Material		PPO dimodifikasi
Material lensa		PMMA

Elemen display/pengoperasian

Display	status peralihan	1 x LED, kuning
	operasi	1 x LED, hijau
	fungsi	1 x LED, merah

Aksesori

Item dikirim		Braket siku obeng
--------------	--	----------------------

Keterangan

Jumlah paket		1 buah
--------------	--	--------

Koneksi listrik

terminal: ...1.5 mm²

Koneksi

