


Through-beam sensor receiver

OGELFNKG/B3/V4A/US-100

Article no longer available - archive entry

Alternative articles: OGE701 + EVC01E

When selecting an alternative article and accessories please note that technical data may differ!



- 1 pushbutton
2 LED \$Justierhilfe

Product characteristics

Type of light	red light
Housing	threaded type

Application

Special feature	Gold-plated contacts; Function check output
Function principle	Through-beam sensor

Electrical data

Operating voltage [V]	10...30 DC
Current consumption [mA]	< 30
Protection class	II
Reverse polarity protection	yes
Type of light	red light
Wave length [nm]	675

Outputs

Electrical design	NPN
Output function	light-on/dark-on mode; (parameterisable)
Max. voltage drop switching output DC [V]	2.5
Function check output	yes
Max. voltage drop of function check output [V]	3.5
Max. current load for function check output [mA]	10
Permanent current rating of switching output DC [mA]	200
Switching frequency DC [Hz]	500
Short-circuit protection	yes



Through-beam sensor receiver

OGELFNKG/B3/V4A/US-100

Type of short-circuit protection	pulsed
Overload protection	yes

Detection zone

Transmitter / receiver	receiver
Range [m]	< 2
Range adjustable	yes
Diameter of the smallest detectable object [mm]	0.5

Operating conditions

Ambient temperature [°C]	-10...50
Protection	IP 67

Tests / approvals

EMC	EN 60947-5-2	
	EN 55011	class B

Mechanical data

Housing	threaded type
Dimensions [mm]	M18 x 1 / L = 72
Thread designation	M18 x 1
Materials	stainless steel (316L/1.4404); PBT
Lens material	PMMA

Displays / operating elements

Display	switching status	1 x LED, yellow
	operation	1 x LED, green
	function	1 x LED, red

Accessories

Items supplied	lock nuts: 2
----------------	--------------

Remarks

Pack quantity	1 pcs.
---------------	--------

Electrical connection

Connector: 1 x M12; coding: A; Contacts: gold-plated






Through-beam sensor receiver

OGELFNKG/B3/V4A/US-100

Connection



2

Function check output