AC2011

AS-Interface module

Moduloberteil aktiv, 1x2E/2AR

Article no longer available - archive entry

Alternative articles: AC5211

When selecting an alternative article and accessories please note that technical data may differ!



1 panel for labelling

Electrical data		
Operating voltage	[V]	26.5...31.6 DC
Current consumption	[mA]	< 135
Max. current load total	[A]	2
Integrated watchdog		no
Inputs / outputs		
Number of inputs and outputs		Number of digital inputs: 2; Number of relay outputs: 2
Inputs		
Number of digital inputs		2
Input circuit of digital inputs		PNP
Sensor supply of the inputs		AS-i
Power supply	[V]	20...30
Max. total current rating of inputs	[mA]	100
Input current High	[mA]	> 5
Input current Low	[mA]	< 1.5
Switching level high	[V]	> 10
Digital inputs protected against short circuits		yes

AC2011

AS-Interface module

Moduloberteil aktiv, 1x2E/2AR

Outputs						
Electrical design		AS-i				
Voltage range DC	[V]	24; (to PELV; via M12 connector)				
Max. current load per output	[mA]	1000; (DC-12)				
Number of relay outputs		2				
Short-circuit proof		no				
Electrically separated		yes				
Operating conditions						
Ambient temperature	[°C]	-25...85				
Protection		IP 67				
Tests / approvals						
EMC		EN 50295				
		EN 50178				
AS-i classification						
AS-i profile		S-3.0				
AS-i I/O configuration	[hex]	3				
AS-i ID code	[hex]	0				
Assignment of the data bits		data bit	D0	D1	D2	D3
		socket	I-1	I-1	O-3	O-4
		pin	4	2	4	4
Mechanical data						
Type of mounting		AS-i interface to FC lower parts				
Materials		PBT				
Displays / operating elements						
Display		operation	LED, green			
		function	LED, yellow			
Remarks						
Remarks		Inputs and outputs must be electrically isolated.				
Pack quantity		1 pcs.				

Electrical connection

contact pins to module lower part, FK / PG:

Connector: M12; coding: A

Connector: M12; coding: A



1	external voltage +
3	external voltage -