IFC217

Inductive sensor

IFG2004-ARKG/M/3,1M/ /PH

Article no longer available - archive entry



Product characteristics		
Electrical design		PNP/NPN
Output function		normally open
Sensing range	[mm]	4
Housing		cylindrical
Dimensions	[mm]	Ø 12
Application		
Application		Use in machine tools, coolants and lubricants
Electrical data		
Operating voltage	[V]	10...36 DC
Protection class		II
Reverse polarity protection		yes
Outputs		
Electrical design		PNP/NPN
Output function		normally open
Max. voltage drop switching output DC	[V]	2.5
Minimum load current	[mA]	2
Max. leakage current	[mA]	0.4

IFC217

Inductive sensor

IFG2004-ARKG/M/3,1M/ /PH

Permanent current rating of switching output DC	[mA]	100	
Switching frequency DC	[Hz]	700	
Short-circuit protection		yes	
Type of short-circuit protection		pulsed	
Overload protection		yes	
Detection zone			
Sensing range	[mm]	4	
Operating distance	[mm]	0...3.25	
Accuracy / deviations			
Correction factor		steel: 1 / stainless steel: 0.7 / brass: 0.5 / aluminium: 0.4 / copper: 0.3	
Hysteresis	[% of Sr]	1...20	
Operating conditions			
Ambient temperature	[°C]	-25...70	
Protection		IP 68; ("Coolant")	
Tests / approvals			
EMC		EN 61000-4-2 ESD	4 kV CD / 8 kV AD
		EN 61000-4-3 HF radiated	10 V/m
		EN 61000-4-4 Burst	2 kV
		EN 61000-4-6 HF conducted	10 V
		EN 55011	class B
Mechanical data			
Housing		cylindrical	
Mounting		non-flush mountable	
Dimensions	[mm]	Ø 12	
Materials		sensing face: LCP; housing: stainless steel; Angle brackets: stainless steel; LED window: PEI	
Displays / operating elements			
Display		switching status	1 x LED, yellow
Remarks			
Pack quantity		1 pcs.	

IFC217

Inductive sensor

IFG2004-ARKG/M/3,1M/ /PH

Electrical connection

Cable: 3.1 m, PUR / PVC; 2 x 0.34 mm²

Connection

	Core colours :
BN =	brown
BU =	blue