RP1317

Incremental encoder with hollow shaft

RP-3600-I05/N10

Article no longer available - archive entry



CE

Product characteristics		
Resolution		3600 resolution
Shaft design		continuous hollow shaft
Shaft diameter	[mm]	20
Electrical data		
Operating voltage tolerance	[%]	10
Operating voltage	[V]	5 DC
Current consumption	[mA]	< 150
Outputs		
Electrical design		TTL
Max. current load per output	[mA]	20
Switching frequency	[kHz]	300
Phase difference A and B	[°]	90
Measuring/setting range		
Resolution		3600 resolution
Operating conditions		
Ambient temperature	[°C]	-30...60
Note on ambient temperature		higher temperature upon request for the diagram see the installation instructions

RP1317

Incremental encoder with hollow shaft

RP-3600-I05/N10

Storage temperature	[°C]		-30...100
Max. relative air humidity	[%]		98
Protection			IP 64
Tests / approvals			
Shock resistance			100 g (6 ms)
Vibration resistance		EN 60068-2-6	200 g (50...2000 Hz)
Mechanical data			
Dimensions	[mm]		Ø 87 / L = 45
Materials			aluminium
Max. revolution, mechanical	[U/min]		6000
Max. starting torque	[Nm]		10
Reference temperature torque	[°C]		20
Shaft design			continuous hollow shaft
Shaft diameter	[mm]		20
Shaft fit			H7
Shaft material			steel (1.4104)
Installation depth of shaft	[mm]		10
Max. axial shaft misalignment	[mm]		1,5

Electrical connection

Cable: 1 m, PUR; radial

brown	A
green	A inverted
grey	B
pink	B inverted
red	0 index
black	0 index inverted
blue	L+ sensor
white	0V sensor
brown/green	L+ (Up)
white/green	0V (Un)
lilac	failure inverted
screen	housing

Diagrams and graphs

Pulse diagram



direction of rotation clockwise (looking at the shaft)