SL0106

Airflow monitor

SLG23CEEAKOA/PH

Article no longer available - archive entry



CE

Product characteristics		
Number of inputs and outputs		Number of relay outputs: 1
Process connection		Ø 23 mm
Application		
Pressure rating	[bar]	1
Electrical data		
Operating voltage	[V]	80...250 AC / 90...250 DC
Reverse polarity protection		no
Inputs / outputs		
Number of inputs and outputs		Number of relay outputs: 1
Outputs		
Output signal		switching signal
Number of relay outputs		1
Contact rating		3 A (30 V DC / 250 V AC)
Switching function flow monitoring		relay energised when flow is present
Short-circuit proof		no
Overload protection		no
Measuring/setting range		
Gases		
Setting range	[cm/s]	100...1000
Greatest sensitivity	[cm/s]	100...400
Accuracy / deviations		
Temperature gradient	[K/min]	5

SL0106

Airflow monitor

SLG23CEEAKOA/PH

Response times			
Response time	[s]	3...60	
Gases			
Response time	[s]	3...60	
Software / programming			
Adjustment of the switch point		potentiometer	
Operating conditions			
Ambient temperature	[°C]	-15...50	
Max. relative air humidity	[%]	90	
Protection		IP 65	
Mechanical data			
Weight	[g]	201	
Dimensions	[mm]	Ø 23	
Materials		housing: PBT; sensor surface: titanium	
Materials (wetted parts)		PBT; titanium	
Process connection		Ø 23 mm	
Displays / operating elements			
Display		function	1 x LED, red
		function	1 x LED, green
Electrical connection			
Required protection		miniature fuse to IEC60127-2 sheet 1; ≤ 5 A; fast acting	
Accessories			
Items supplied		Mounting clamp: 1, E40048	
		screwdrivers	
Remarks			
Remarks		Recommendation Check the safe functioning of the unit after a short circuit.	
Pack quantity		1 pcs.	

SL0106

Airflow monitor

SLG23CEEAKOA/PH

Electrical connection

Cable: 2 m, PUR; 4 x 0.5 mm², PVC

Connection



Note miniature fuse to IEC60127-2 sheet 1 ≤ 5 A fast acting
Core colours :

BN =	brown
BU =	blue
BK =	black
WH =	white