



Recalibration for infrared temperature sensors

Rekalibrierung für Infrarot-Temp. TW200x

**Werkskalibrierschein**  
Factory calibration certificate

  

<p><b>Messumformer-Typ:</b> TW200 transmitter type:</p> <p><b>Serien-Nr.:</b> 11111111 serial no.:</p> <p><b>Messbereich:</b> 1...100°C temperature range:</p> <p><b>Ausgangssignal:</b> 1...5V output:</p> <p><b>Genauigkeit:</b> ±1.0% accuracy:</p> <p><b>Kalibrierdatum:</b> 11.11.11 date of calibration:</p>	<p><b>Auftragsnummer:</b> 111111 job no.:</p> <p><b>Referenzgerät:</b> 111111 reference unit:</p> <p><b>Prüfnorm, Temperatur:</b> 111111 testing device, temperature:</p> <p><b>Serien-Nr.:</b> 111111 serial no.:</p> <p><b>PTB-Zertifikat:</b> 111111 PTB certificate:</p> <p><b>Umgebungstemperatur:</b> 11.11.11 ambient temperature:</p>
--	---

  

11.11.11	11.11.11	11.11.11
11.11.11	11.11.11	11.11.11
11.11.11	11.11.11	11.11.11

  

*(The following text is a blurred German calibration certificate. It contains technical details about the sensor's accuracy and calibration process.)*

**Mechanical data**

<b>Weight</b>	[g]	20.8
---------------	-----	------

**Remarks**

<p>Remarks</p>	<p style="text-align: center;">The device has to be returned to supplier.</p> <p style="text-align: center;">The corresponding sensor is delivered along with the calibration certificate.</p> <p style="text-align: center;">The calibration certificate is in two languages (German/English).</p> <p style="text-align: center;">Subsequent orders are only possible if the sensor is in a clean condition upon return.</p> <p style="text-align: center;">In the internet version of the data sheet a sample certificate is stored in the tab "Downloads".</p>
----------------	---