DD1001

Evaluation unit for speed monitoring

D100/230VAC/3LED

Article no longer available - archive entry



1 mounting on DIN rail

CE

Product characteristics		
Housing		housing for DIN rail mounting
Dimensions	[mm]	75 x 55 x 110
Application		
Application		universal evaluation of pulse sequences with regard to overspeed and underspeed; rotational speed monitoring
Electrical data		
Nominal voltage AC	[V]	< 230
Nominal voltage DC	[V]	24
Nominal voltage tolerance	[%]	10
Nominal voltage tolerance 2	[%]	10
Nominal frequency AC	[Hz]	50...60
Auxiliary energy for sensors DC	[V]	24; (≤ 30 mA)
Inputs / outputs		
Number of inputs and outputs		Number of relay outputs: 1
Outputs		
Number of relay outputs		1
Contact rating		8 A / 1250 VA / 250 V AC
Measuring/setting range		
Setting range	[Imp/min]	500...5000
Accuracy / deviations		
Hysteresis	[% of Sr]	5...100
Repeatability	[% of Sr]	1

DD1001

Evaluation unit for speed monitoring

D100/230VAC/3LED

Response times			
Start-up delay	[s]	0.5...15	
Software / programming			
Adjustment of the switch point		fine adjustment within the range with potentiometer	
Operating conditions			
Ambient temperature	[°C]	-20...70	
Protection		IP 40	
Protection rating terminals		IP 20	
Mechanical data			
Housing		housing for DIN rail mounting	
Dimensions	[mm]	75 x 55 x 110	
Materials		plastics	
Displays / operating elements			
Display		switching status	LED, green
		operation	1 x LED, green
Electrical connection			
Connection