DX2003

Multifunction display for monitoring revolution, speed and time

DISPLAY/FX360/PNP OUT

Article no longer available - archive entry

Alternative articles: DX2023

When selecting an alternative article and accessories please note that technical data may differ!



CE

Application			
Application			universal evaluation and display for all physical units which can be derived from pulse sequences
Electrical data			
Frequency AC	[Hz]		50...60
Operating voltage tolerance	[%]		33...58
Operating voltage	[V]		230 / 115 AC / 24 DC
Current consumption	[mA]		120 (18 V); 95 (24 V); 80 (30 V)
Auxiliary energy for sensors DC	[V]		24; (±15 %, 150 mA)
Operating conditions			
Ambient temperature	[°C]		0...45
Storage temperature	[°C]		-25...75
Protection			IP 65; (on the front)
Protection rating terminals			IP 20
Tests / approvals			
EMC		EN 50081-1	
		EN 61000-6-2	
Mechanical data			
Weight	[g]		575.4

DX2003

Multifunction display for monitoring revolution, speed and time

DISPLAY/FX360/PNP OUT

Materials	Noryl UL94-V-0

Displays / operating elements

Display	7-segment LED display, orange 6-digit 15 mm

Electrical connection

screw terminals, DC: 10 x ...1.5 mm²

screw terminals, AC: 4 x ...2.5 mm²

Connection