MK5044

Cylinder sensor for tie-rod cylinder

MKZ3000-BPKG/5M

Article no longer available - archive entry



1 sensing face

CE

Product characteristics		
Electrical design		PNP
Output function		normally open
Dimensions	[mm]	30 x 30 x 23
Electrical data		
Operating voltage	[V]	10...30 DC
Current consumption	[mA]	< 10
Reverse polarity protection		yes
Max. power-on delay time	[ms]	2
Outputs		
Electrical design		PNP
Output function		normally open
Max. voltage drop switching output DC	[V]	2
Permanent current rating of switching output DC	[mA]	300
Switching frequency DC	[Hz]	5000
Short-circuit protection		yes
Type of short-circuit protection		pulsed
Overload protection		yes
Detection zone		
Response sensitivity	[mT]	3
Travel speed	[m/s]	< 5

MK5044

Cylinder sensor for tie-rod cylinder

MKZ3000-BPKG/5M

Accuracy / deviations			
Hysteresis	[mm]	1	
Repeatability	[mm]	0.1	
Operating conditions			
Ambient temperature	[°C]	-25...75	
Protection		IP 67	
Tests / approvals			
EMC		EN 60947-5-2	
Shock/vibration resistance		30 g (11 ms) / 10-55 Hz (1 mm)	
Mechanical data			
Sensing face		front	
Cylinder type		tie rod cylinders	
Dimensions	[mm]	30 x 30 x 23	
Materials		aluminium; plastics	
Displays / operating elements			
Display		switching status	1 x LED, yellow
Remarks			
Pack quantity		1 pcs.	
Electrical connection			

Cable: 5 m, PUR / PVC; 3 x 0.25 mm²

Connection



	Core colours :
BN =	brown
BU =	blue
BK =	black