


AS-Interface ClassicLine module

ClassicLine45 4DI FKT M12

Article no longer available - archive entry



- 1 panel for labelling
2 fixture infrared adapter



Electrical data

Operating voltage	[V]	26.5...31.6 DC
Max. current consumption from AS-i	[mA]	250

Inputs / outputs

Number of inputs and outputs	Number of digital inputs: 4
------------------------------	-----------------------------

Inputs

Number of digital inputs		4
Input circuit of digital inputs		PNP
Sensor supply of the inputs		AS-i
Power supply	[V]	18...30; (via flat cable)
Max. total current rating of inputs	[mA]	200
Input current High	[mA]	6...10
Input current Low	[mA]	0...2
Switching level high	[V]	> 11
Digital inputs protected against short circuits		yes

Outputs

Electrical design	AS-i
-------------------	------

Operating conditions

Ambient temperature	[°C]	-25...50
---------------------	------	----------



AS-Interface ClassicLine module

ClassicLine45 4DI FKT M12

Note on ambient temperature	current for sensor supply: < 200 mA
	-25...70 °C: < 150 mA
Protection	IP 67

Tests / approvals

EMC	EN 50295
-----	----------

AS-i classification

AS-i version	2.1					
AS-i addressing	IR addressing possible					
Extended addressing mode	no					
AS-i profile	S-0.F.E					
AS-i I/O configuration [hex]	0					
AS-i ID code [hex]	F.E					
Assignment of the parameter bits	parameter bit	Designation				
	P0	selection High active / Low active	/	pin	2 /	socket I-1 / FKT 1
	P1	selection High active / Low active	/	pin	2 /	socket I-2 / FKT 2
	P2	selection High active / Low active	/	pin	2 /	socket I-3 / FKT 3
	P3	selection High active / Low active	/	pin	2 /	socket I-4 / FKT 4

Mechanical data

Weight [g]	107.7
Type of mounting	AS-i interface to FC lower parts
Materials	PBT

Displays / operating elements

Display	operation	LED, green
	errors	LED, red
	function	LED, yellow

Accessories

Accessories (optional)	Module lower part
------------------------	-------------------

Remarks

Remarks	Do not connect any of the following points to an external potential:
	I-, I+, I1...I4, FKT1...FKT4
	The connections are electrically connected with the AS-i cable.
	In case of a fault the high or low activity (NO or NC principle) of the function check inputs can be set separately.
	In case of a fault the red LED of the corresponding input lights and in addition LED 2 (FAULT) flashes.
Pack quantity	1 pcs.



AS-Interface ClassicLine module

ClassicLine45 4DI FKT M12

Electrical connection

contact pins to module lower part, FK / PG:

Connector: M12; coding: A



	Inputs
1	Sensor supply L+
2	function check input
3	Sensor supply L-
4	data input
5	not used