DD2605

Evaluation unit for speed monitoring

MONITOR/FR-2N/110-240VAC/DC

Article no longer available - archive entry

Alternative articles: DD2505
When selecting an alternative article and accessories please note that technical data may differ!



1 OLED display
2 programming buttons
3 LEDs

Product characteristics		
Housing		housing for DIN rail mounting
Dimensions	[mm]	78 x 45 x 124.7
Application		
Application		pulse evaluation system with microprocessor for frequency; rotational speed; speed; pulses and machine cycles
Electrical data		
Nominal voltage AC	[V]	110...240
Nominal voltage DC	[V]	27
Nominal voltage tolerance	[%]	< 10
Nominal voltage tolerance 2	[%]	20...10
Nominal frequency AC	[Hz]	50...60
Power consumption	[W]	3
Auxiliary energy for sensors DC	[V]	8.2
Inputs / outputs		
Number of inputs and outputs		Number of relay outputs: 2
Outputs		
Number of relay outputs		2
Contact rating		6 A (250 V AC); B300, R300
Measuring/setting range		
Setting range Hz	[Hz]	0.1...1000

DD2605

Evaluation unit for speed monitoring

MONITOR/FR-2N/110-240VAC/DC

Setting range [Imp/min]	1...60000	
Operating conditions		
Ambient temperature [°C]	-40...60	
Storage temperature [°C]	-40...85	
Max. relative air humidity [%]	80; (40 °C: 50 %)	
Protection	IP 50	
Protection rating terminals	IP 20	
Tests / approvals		
EMC	EN 61010	2011
	EMV 89/336/EWG	
	EN 61000-6-2	: 2005
	EN 61000-6-4	2007
Mechanical data		
Weight [g]	381.5	
Housing	housing for DIN rail mounting	
Dimensions [mm]	78 x 45 x 124.7	
Materials	plastics	
Displays / operating elements		
Display		OLED display, 128 x 64 pixels luminous
	switching status	LED, green
Remarks		
Remarks	The unit complies with overvoltage category II; pollution degree 2	

Electrical connection

dual-chamber terminals: 2 x ...2.5 mm²; AWG 14

1	DC supply voltage (L-)
2	DC supply voltage (L+)
3	current supply transistor outputs (L+)
4	error output 1
5	8.2 V DC Sensor supply 1 (L-)
6	8.2 V DC Sensor supply 1 (L+)
7	AC supply voltage (L)
8	AC supply voltage (N)
9	not used
10	error output 2
11	8.2 V DC Sensor supply 2 (L-)
12	8.2 V DC Sensor supply 2 (L+)
13	relay 1 common
14	relay 1 normally open
15	relay 1 normally closed
16	transistor output 1 pnp
17	reset 1 pnp
18	reset 2 pnp
19	relay 2 common
20	relay 2 normally open
21	relay 2 normally closed
22	not used
23	not used
24	transistor output 2 pnp