OE0005

Through-beam sensor receiver






Article no longer available - archive entry

Alternative articles: OE0002

When selecting an alternative article and accessories please note that technical data may differ!



Product characteristics		
Type of light		infrared light
Housing		threaded type
Application		
Function principle		Through-beam sensor
Electrical data		
Connection to switching amplifiers		yes
Switching amplifiers		Connection to switching amplifiers OV5012, OV0010
Protection class		III
Type of light		infrared light
Wave length	[nm]	950
Outputs		
Short-circuit protection		no
Overload protection		no
Detection zone		
Transmitter / receiver		receiver
Range	[m]	<1
Operating conditions		
Ambient temperature	[°C]	-2080
Protection		IP 67

OE0005

Through-beam sensor receiver

Core colours :

white

screen

WH =

screen =





Tests / approvals		
EMC		EN 60947-5-2
MTTF	[years]	49633
Mechanical data		
Weight	[g]	0.126
Housing		threaded type
Dimensions	[mm]	M8 x 1
Thread designation		M8 x 1
Materials		brass nickel-plated
Accessories		
Items supplied		lock nuts: 2
Remarks		
Pack quantity		1 pcs.
Electrical connection		
Cable: 10 m; 1 x 0.14 mi	m²	
Connection		
		WH
		I ♠ F
		screen