RB6043

Incremental encoder with solid shaft

RB-0360-I24/L2E

Article no longer available - archive entry



1 reference mark
2 M3 Depth 5 mm

Product characteristics		
Resolution		360 resolution
Shaft design		solid shaft
Shaft diameter	[mm]	6
Electrical data		
Operating voltage	[V]	10...30 DC
Current consumption	[mA]	150
Outputs		
Electrical design		HTL
Max. current load per output	[mA]	50
Switching frequency	[kHz]	160
Type of short-circuit protection		< 60 s
Phase difference A and B	[°]	90
Measuring/setting range		
Resolution		360 resolution
Operating conditions		
Ambient temperature	[°C]	-20...70
Storage temperature	[°C]	-30...100
Max. relative air humidity	[%]	98
Protection		IP 66
Tests / approvals		
Shock resistance		100 g (6 ms)
Vibration resistance		10 g (55...2000 Hz)
Mechanical data		
Dimensions	[mm]	Ø 36.5 / L = 38
Materials		aluminium

RB6043

Incremental encoder with solid shaft

RB-0360-I24/L2E

Max. revolution, mechanical	[U/min]	10000
Max. starting torque	[Nm]	1
Reference temperature torque	[°C]	20
Shaft design		solid shaft
Shaft diameter	[mm]	6
Shaft material		steel (1.4104)
Max. shaft load axial (at the shaft end)	[N]	5
Max. shaft load radial (at the shaft end)	[N]	10

Electrical connection

Cable: 2 m, PUR; radial, can also be used axially

white/green	0V
brown/green	L+
brown	A
green	0V A
grey	B
pink	0V B
red	0 index
black	0V 0 index
lilac	failure inverted
screen	housing

Diagrams and graphs

Pulse diagram



direction of rotation clockwise (looking at the shaft)