



ISO-kalibreringscertifikat för temperaturgivare n-punkts

ISO-Kalibrierung Temp. N-Pkt

Werkskalibrierschein
Factory calibration certificate

Messumformer-Typ: PT1000
transmitter type: PT1000
Serien-Nr.: 1000000
serial no.: 1000000
Messbereich: -20...150 °C
temperature range: -20...150 °C
Ausgangssignal: 4...20 mA
output: 4...20 mA
Genauigkeit: ±0,1 °C
accuracy: ±0,1 °C
Kalibrierdatum: 10.10.2012
date of calibration: 10.10.2012

Auftragsnummer: 1000000
job no.: 1000000
Referenzgerät: PT1000
reference unit: PT1000
Prüfnorm, Temperatur: PT1000
testing device, temperature: PT1000
Serien-Nr.: 1000000
serial no.: 1000000
PTB-Zertifikat: PTB-Zertifikat
Umgebungstemperatur: 20 °C
ambient temperature: 20 °C

The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard. The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard.

The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard. The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard.

The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard. The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard.

The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard. The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard.

The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard. The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard.

The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard. The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard.

The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard. The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard.

The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard. The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard.

The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard. The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard.

The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard. The calibration was performed in accordance with the requirements of the "Technical Regulation" of the PTB (Physikalisch-Technische Bundesanstalt) and the requirements of the ISO 9001:2008 standard.

Mekaniska data	
Vikt	[g] 19,171
Anmärkning	
Anmärkning	ISO-kalibreringscertifikatet erkänns inte enligt EA MLA (Multilateral Agreement) och anses därför inte vara spårbart. Kalibreringscertifikatet måste beställas i samband med en givare. Motsvarande givare levereras tillsammans med kalibreringscertifikatet. Kalibreringscertifikatet är utfärdat på två språk (tyska/engelska). Efterföljande order är endast möjlig om givaren är i ett rent skick vid återlämnandet. I internetversionen av databladet finns exempel på ett certifikat under fliken "Nedladdningar". max. 4 mätpunkter kan väljas enligt kundens önskemål Temperaturområde -20°C...150°C