# LMT302

## Sensor for point level detection

LMCCE-A01E-QSKG-2/US




1 Tightening torque 35 Nm

ACS EC 1935/2004 IO-Link KTW/W270

| | | |
|---|---|---|
| **Product characteristics** | | |
| Number of inputs and outputs | | Number of digital outputs: 2 |
| Factory setting | | hydrous media |
| Process connection | | G 1 external thread |
| **Application** | | |
| Special feature | | Gold-plated contacts |
| Installation | | suited for installation in existing tuning fork adapters |
| Media | | Liquids; viscous media; powder |
| Recommended media | | water; hydrous media; oils; oil-based media; powder |
| Cannot be used for | | See the operating instructions, chapter "Function and features". |
| Probe length | [mm] | 38 |
| Tank pressure | [bar] | -1...40 |
| Oil | | |
| Medium temperature | [°C] | -20...100 |
| Medium temperature short time | [°C] | -20...150; (1 h) |
| Water | | |
| Medium temperature | [°C] | -20...100 |
| Medium temperature short time | [°C] | -20...150; (1 h) |
| **Electrical data** | | |
| Operating voltage | [V] | 18...30 DC |
| Current consumption | [mA] | < 50 |
| Protection class | | III |
| Reverse polarity protection | | yes |
| Measuring principle | | capacitive |
| **Inputs / outputs** | | |
| Number of inputs and outputs | | Number of digital outputs: 2 |

# LMT302

## Sensor for point level detection

LMCCE-A01E-QSKG-2/US

| | | | |
|---|---|---|---|
| **Outputs** | | | |
| Total number of outputs | | 2 | |
| Output signal | | switching signal; IO-Link | |
| Electrical design | | PNP/NPN | |
| Number of digital outputs | | 2 | |
| Output function | | normally open / normally closed; (parameterisable) | |
| Max. voltage drop switching output DC | [V] | 2.5 | |
| Permanent current rating of switching output DC | [mA] | 100 | |
| Short-circuit protection | | yes | |
| Type of short-circuit protection | | pulsed | |
| Overload protection | | yes | |
| **Measuring/setting range** | | | |
| Factory setting | | hydrous media | |
| **Response times** | | | |
| Response time | [s] | < 0.5 | |
| **Interfaces** | | | |
| Communication interface | | IO-Link | |
| Transmission type | | COM2 (38,4 kBaud) | |
| IO-Link revision | | 1.1 | |
| SDCI standard | | IEC 61131-9 | |
| Profiles | | Smart Sensor: Process Data Variable; Device Identification | |
| SIO mode | | yes | |
| Required master port type | | A | |
| Process data analogue | | 1 | |
| Process data binary | | 2 | |
| Min. process cycle time | [ms] | 2.3 | |
| Supported DeviceIDs | | **Type of operation** | **DeviceID** |
| | | default | 370 |
| **Operating conditions** | | | |
| Ambient temperature | [°C] | -20...85 | |
| Note on ambient temperature | | Medium temperature: < 100 °C | |
| | | -20...60 °C | |
| | | Medium temperature: < 150 °C | |
| Storage temperature | [°C] | -40...85 | |
| Protection | | IP 68; IP 69K | |
| **Tests / approvals** | | | |
| EMC | | DIN EN 61000-6-2 | : 2006 |
| | | DIN EN 61000-6-4 | : 2011 / open tanks |
| | | DIN EN 61000-6-3 | : 2011 / closed tanks |
| Shock resistance | | DIN EN 60068-2-27 | 50 g (11 ms) |
| Vibration resistance | | DIN EN 60068-2-6 | 20 g (10...2000 Hz) |
| MTTF | [years] | 223 | |

# LMT302

## Sensor for point level detection

LMCCE-A01E-QSKG-2/US

| | | | |
|---|---|---|---|
| UL approval | | UL Approval no. | H001 |
| **Mechanical data** | | | |
| Weight | [g] | 391 | |
| Dimensions | [mm] | Ø 30 / L = 125.5 | |
| Materials | | stainless steel (316L/1.4404); PEEK; PEI; FKM | |
| Materials (wetted parts) | | PEEK; surface characteristics: Ra < 0,8 / Rz 4 | |
| Process connection | | G 1 external thread | |
| **Displays / operating elements** | | | |
| Display | | switching status | LED, yellow |
| | | operating status | LED, green |
| **Remarks** | | | |
| Pack quantity | | 1 pcs. | |

**Electrical connection**

Connector: 1 x M12; coding: A; Contacts: gold-plated

Connection




| | |
|---|---|
| OUT1: | switching output IO-Link Teach |
| OUT2: | switching output |
| | colours to DIN EN 60947-5-2 |