



Certifikat ISO za umerjanje za n-točkovne temperaturne senzorje

ISO-Kalibrierung Temp. N-Pkt

Werkskalibrierschein
Factory calibration certificate

Messumformer-Typ: PT1000
transmitter type: PT1000
Serien-Nr.: 10000000
serial no.: 10000000
Messbereich: -20...150 °C
temperature range: -20...150 °C
Ausgangssignal: 4...20 mA
output: 4...20 mA
Genauigkeit: ± 0,15 °C
accuracy: ± 0,15 °C
Kalibrierdatum: 10.05.2012
date of calibration: 10.05.2012

Auftragsnummer: 10000000
job no.: 10000000
Referenzgerät: PT1000
reference unit: PT1000
Prüfnormal, Temperatur: PT1000
testing device, temperature: PT1000
Serien-Nr.: 10000000
serial no.: 10000000
PTB-Zertifikat: PTB-Zertifikat
PTB certificate: PTB certificate
Umgebungstemperatur: 20 °C
ambient temperature: 20 °C

The calibration was performed in accordance with the requirements of the PTB (Physikalisch-Technische Bundesanstalt) and the DIN EN ISO 9001:2008 standard. The calibration was performed in accordance with the requirements of the PTB (Physikalisch-Technische Bundesanstalt) and the DIN EN ISO 9001:2008 standard. The calibration was performed in accordance with the requirements of the PTB (Physikalisch-Technische Bundesanstalt) and the DIN EN ISO 9001:2008 standard.

The accuracy of the measurement is ± 0,15 °C. The accuracy of the measurement is ± 0,15 °C. The accuracy of the measurement is ± 0,15 °C.

The accuracy of the measurement is ± 0,15 °C. The accuracy of the measurement is ± 0,15 °C. The accuracy of the measurement is ± 0,15 °C.

The accuracy of the measurement is ± 0,15 °C. The accuracy of the measurement is ± 0,15 °C. The accuracy of the measurement is ± 0,15 °C.

The accuracy of the measurement is ± 0,15 °C. The accuracy of the measurement is ± 0,15 °C. The accuracy of the measurement is ± 0,15 °C.

Mehanski podatki

Teža	[g]	19,171
------	-----	--------

Opombe

Opombe	potrdilo o umerjanju ISO ni priznано skladno z EA MLA (večstranski sporazum) in se zato šteje, da se mu ne sledi. Certifikat za umerjanje je treba naročiti v povezavi s senzorjem. Ustrezni senzor je dobavljen skupaj s certifikatom za umerjanje. Certifikat za umerjanje je na voljo v dveh jezikih (nemško/angleško). Naknadna naročila so mogoča le, če je senzor ob vrnitvi čist. V spletni različici lista s podatki je vzorčni certifikat shranjen pod zavihkom »Prenosi«. maks. 4 merilne točke je mogoče izbrati glede na strankine zahteve Temperaturno območje -20°C...150°C
--------	---