

Technical drawing of the LED module showing front and side views with dimensions.

Front View Dimensions:

- Overall width: 54
- Overall height: 82
- Distance between LED centers (vertical): 73
- Distance between LED centers (horizontal): 33
- LED diameter: 12 (M12x1)
- LED mounting hole diameter: 4.5
- LED label: LED

Side View Dimensions:

- Module thickness: 18
- LED mounting hole diameter: 9

Provozní napětí	[M]	10...110 AC/DC
Max. aktuální zatížitelnost na modul / slot	[A]	4
Max. aktuální zatížitelnost celkem	[A]	12

Okolní teplota	[°C]	-15...90
Krytí		IP 67

Rozměry [mm]	18 x 54 x 82
Počet portů centrálního rozvaděče	4

Obsah balení	1 ks
--------------	------



Centrální rozvaděč


ZDO4H040MSS0010A07

Elektrické připojení

Kabel: 10 m, PUR / PVC; 4 x 0,34 mm² + 3 x 0,75 mm²

Elektrické připojení - slot

konektorové provedení: 4 x M12; kódování: A



Připojení

BN	1 (1...4)	C
BU	3 (1...4)	C
GN/YE	5 (1...4)	C
WH	4 (1)	C
GN	4 (2)	C
YE	4 (3)	C
GY	4 (4)	C

	Barvy vodičů :
BN =	hnědá
BU =	modrá
GN =	zelená
GN/YE =	zelená / žlutá
GY =	šedá
WH =	bílá
YE =	žlutá