DN0213

Switching amplifier

N600/110VAC/0,08A



Article no longer available - archive entry

Alternative articles: DN0200

When selecting an alternative article and accessories please note that technical data may differ!

No scale drawing available

ϵ

| B 1 4 1 4 1 2 | | |
|---------------------------------|------|------------------------------------|
| Product characteristics | | |
| Housing | | housing for DIN rail mounting |
| Dimensions | [mm] | 75 x 55 x 110 |
| Application | | |
| Application | | Power supply and signal evaluation |
| Electrical data | | |
| Nominal voltage AC | [V] | < 110 |
| Nominal voltage tolerance | [%] | 10 |
| Nominal voltage tolerance 2 | [%] | 10 |
| Nominal frequency AC | [Hz] | 4763 |
| Auxiliary energy for sensors DC | [V] | 24; (±5 %, ≤ 40 mA) |
| Outputs | | |
| Contact rating | | 4 A / 625 VA / 250 V AC |
| Operating conditions | | |
| Ambient temperature | [°C] | 050 |
| Protection | | IP 40 |
| Protection rating terminals | | IP 20 |
| Mechanical data | | |
| Housing | | housing for DIN rail mounting |
| Dimensions | [mm] | 75 x 55 x 110 |

DN0213

Switching amplifier

N600/110VAC/0,08A



| Materials | | plastics | | | |
|--------------------------|------------------|----------------|--|--|--|
| Displays / operating ele | ements | | | | |
| Display | switching status | LED, green | | | |
| | operation | 1 x LED, green | | | |
| Electrical connection | | | | | |
| terminals:4 mm² | | | | | |
| Connection | | | | | |