ZC0053

流動感測器ISO校準證書

ISO calibration SU device



Werkskalibrierschein		ifm	electronic 🞹	
Factory calibration certificate				
Messumformer-Typ:	1000	Auftragsnummer:		
transmitter type: Serien-Nr.:		job no.: Referenzgerät:		
serial no.:		reference unit:		
Messbereich:	1.00017	Prüfnormal, Temperatur:		
temperature range: Ausgangssignal:	1.000	testing device, temperature: Serien-Nr.:		
output:		serial no.:		
Genauigkeit:	111000-0010	PTB-Zertifikat: PTB certificate:		
accuracy: Kalibrierdatum:	0.000	Umgebungstemperatur:		
date of calibration:		ambient temperature:		
7 2 21 21	H.			
Ryconorter de Youghtis Ne unitentre set anglés	national in American all the first			
Aproximo de fragiste for adminis en político procisione impreligio	-	e (nationales fromprister frantisch saf- tual salledor all sighters product is on	Back do: TO M.	
To be the second	and the second state of th	e balloudes longerate frankrik od		
		and the State of t		
	and the second state of th	in colondo forget de familie de se de freibefalte de Wesselde secto locidos de al des depos		
		e publicados fungarados fundados del las cilhatos del cigliano promos e con a acedes finisherholes de Wesserhol concris facilitan del ad disco disposa a gife resouvere radial acide all cali cale o la cica.	Back do FT N. price offices back mass and draw do the felicitoropol of the felicitoropol of the felicitoropol of	
		continued or frequency of the State of the S	had do FI N. price of these backs may not dean do the felicitoropol of the felicitoropol of	
	The second secon	continued or frequency of the State of the S	had do 10 M. pro- of the barries the balance of the Ar- tion balance	
	and the second of the second o	in colonials from the familials of the colonials of the c	Back der FO M. The control described in the c	
Management of the party of the	and the control of th	in a des interaction parties and the control of the		
	and the control of th	in colonials from the familials of the colonials of the c		

應用				
設計		應用於型號 SUxx0x		
機械技術數據				
重量	[g]	33.17		
注釋				
注釋		校準證書須與相應的感測器一起訂購。		
		相應的感測器與校準證書一起供貨。		
		校準證書為兩種語言(德語/英語)。		
		如果感測器乾凈無損地返回,後續訂單才可能。		
		在因特網技術資料裏,示例證書存儲在選項"下載"中。		