E33071

Mounting adapter for process sensors

ADAPT IFM-SMS DN40(1.5)GWD



1 Aseptoflex thread 2 Aseptoflex sealing edge Application Pressure rating [bar] 25 Tests / approvals Pressure Equipment Directive Aseptoflex instructions Compatibility between medium and product material has to be checked in all applications. Materials Statiness steel (1.4404 / 316L) Sensor connection		
2 Aseptoflex sealing edge Application Pressure rating [bar] 25 Tests / approvals Pressure Equipment Directive A possible classification to PED depends on the application and has to be carried out by the user / operator. Safety instructions The compatibility between medium and product material has to be checked in all applications. Materials Stainless steel (1.4404 / 316L)		
Pressure rating[bar]25Tests / approvalsA possible classification to PED depends on the application and has to be carried out by the user / operator.Safety instructionsThe compatibility between medium and product material has to be checked in all applications.Mechanical dataStainless steel (1.4404 / 316L)	1Aseptoflex thread2Aseptoflex sealing edge	
Tests / approvals Pressure Equipment Directive A possible classification to PED depends on the application and has to be carried out by the user / operator. Safety instructions The compatibility between medium and product material has to be checked in all applications. Mechanical data Stainless steel (1.4404 / 316L)	Application	
Pressure Equipment Directive A possible classification to PED depends on the application and has to be carried out by the user / operator. Safety instructions The compatibility between medium and product material has to be checked in all applications. Mechanical data Stainless steel (1.4404 / 316L)	Pressure rating [bar]	25
application and has to be carried out by the user / operator. Safety instructions The compatibility between medium and product material has to be checked in all applications. Mechanical data Materials Stainless steel (1.4404 / 316L)	Tests / approvals	
material has to be checked in all applications. Mechanical data Materials stainless steel (1.4404 / 316L)	Pressure Equipment Directive	
Materials stainless steel (1.4404 / 316L)	Safety instructions	
	Mechanical data	
Sensor connection Acontofley	Materials	stainless steel (1.4404 / 316L)
	Sensor connection	Aseptoflex
Process connection flange DN40 (1,5")		flange DN40 (1,5")
Surface characteristics Ra/Rz 0.4 / 4 of the wetted parts 0.4 / 4		
Hygienic equipment class to DIN 11866 H4	Process connection Surface characteristics Ra/Rz	0.4 / 4
Remarks	Process connection Surface characteristics Ra/Rz of the wetted parts Hygienic equipment class to	
Pack quantity 1 pcs.	Process connection Surface characteristics Ra/Rz of the wetted parts Hygienic equipment class to DIN 11866	