

OGP-DBOW/LS/CUBE

Technical drawing of the LED module showing front and side views with dimensions:

- Front View (Left):**
 - Total width: 36,9
 - Distance from mounting hole to LED center: 15,7
 - Distance between mounting holes: 12,2
 - Total height: 52,6
 - Distance from mounting hole to LED center (height): 24,1
 - Mounting hole diameter: $\varnothing 3,2$
 - Thread: 1/2" - 20 UNF
 - LED module width: M18 x 1
 - Mounting hole pitch: 24
- Side View (Right):**
 - LED module width: 19,1
 - LED module height: 38,4
 - LEDs are indicated by a label pointing to the module.



Type of light	red light
Housing	rectangular with M18 thread

Special feature	polarisation filter
Function principle	Retro-reflective sensor

Frequency AC	[Hz]	47...63
Operating voltage	[V]	20...250 AC
Protection class		II; (double insulated)
Type of light		red light
Wave length	[nm]	633

Output function	dark-on mode
Max. voltage drop switching output AC [V]	8
Minimum load current [mA]	5
Max. leakage current [mA]	1.7
Permanent current rating of switching output AC [mA]	150; (200 (...40 °C))
Short-time current rating of switching output [mA]	1200; (20 ms / 0,5 Hz)
Switching frequency AC [Hz]	30
Short-circuit protection	no
Overload protection	no



Retro-reflective sensor


OGP-DBOW/LS/CUBE

Detection zone		
Range referred to prismatic reflector	[m]	4; (Prismatic reflector Ø 80 E20005)
Range adjustable		no
Max. light spot diameter	[mm]	160
Light spot dimensions refer to		at maximum range
Polarisation filter available		yes
Operating conditions		
Ambient temperature	[°C]	-25...60
Protection		IP 67
Tests / approvals		
EMC	EN 60947-5-2	
	EN 55011 emission	class B
Mechanical data		
Weight	[g]	61.5
Housing		rectangular with M18 thread
Dimensions	[mm]	52.6 x 19.1 x 36.9
Thread designation		M18 x 1
Materials		diecast zinc; PEI
Lens material		PMMA
Lens alignment		side lens
Displays / operating elements		
Display	switching status	1 x LED, yellow
Electrical connection		
Required protection		miniature fuse to IEC60127-2 sheet 1; ≤ 2 A; fast acting
Аксессуары		
Items supplied		lock nut: 1
Remarks		
Remarks		Do not connect without a load.
Pack quantity		1 pcs.
Electrical connection		
Connector: 1 x 1/2"; coding: C		
		

Retro-reflective sensor

OGP-DBOW/LS/CUBE


Connection



Note : miniature fuse to IEC60127-2 sheet 1 ≤ 2 A fast acting

Diagrams and graphs

excess gain graph



x: Abstand [m]

y: Funktionsreservefaktor