



Recalibration for LDP oil particle monitor

Rekalibrierung für Particle Monitor

Werkskalibrierschein
Factory calibration certificate

Messumformer-Typ: 75000
transmitter type:

Serien-Nr.: 12345678
serial no.:

Messbereich: 1...1000 L/min
temperature range:

Ausgangssignal: 1...10V
output:

Genauigkeit: ±1.0%
accuracy:

Kalibrierdatum: 12.03.2017
date of calibration:

Auftragsnummer: 123456
job no.:

Referenzgerät: 12345678
reference unit:

Prüfnormal, Temperatur: 20°C
testing device, temperature:

Serien-Nr.: 12345678
serial no.:

PTB-Zertifikat: 12345678
PTB certificate:

Umgebungstemperatur: 20°C
ambient temperature:

The calibration was performed at the ifm electronic calibration center in the "reference unit" with the reference transmitter as "test device" in accordance with the German technical standards and standards of the PTB.

The calibration was performed in the laboratory temperature of 20°C. The reference unit is a reference unit in accordance with the requirements of the PTB.

The accuracy of the measurement results is determined by the accuracy of the reference unit and the accuracy of the calibration process. The measurement results are valid for the duration of the calibration.

The accuracy of the measurement results is determined by the accuracy of the reference unit and the accuracy of the calibration process. The measurement results are valid for the duration of the calibration.

The accuracy of the measurement results is determined by the accuracy of the reference unit and the accuracy of the calibration process. The measurement results are valid for the duration of the calibration.

The accuracy of the measurement results is determined by the accuracy of the reference unit and the accuracy of the calibration process. The measurement results are valid for the duration of the calibration.

The accuracy of the measurement results is determined by the accuracy of the reference unit and the accuracy of the calibration process. The measurement results are valid for the duration of the calibration.

The accuracy of the measurement results is determined by the accuracy of the reference unit and the accuracy of the calibration process. The measurement results are valid for the duration of the calibration.

The accuracy of the measurement results is determined by the accuracy of the reference unit and the accuracy of the calibration process. The measurement results are valid for the duration of the calibration.

Mechanical data	
Weight	[g] 20.7
Remarks	
Remarks	<p>The device has to be returned to supplier.</p> <p>The corresponding sensor is delivered along with the calibration certificate.</p> <p>The calibration certificate is in two languages (German/English).</p> <p>Subsequent orders are only possible if the sensor is in a clean condition upon return.</p> <p>In the internet version of the data sheet a sample certificate is stored in the tab "Downloads".</p>