


# ANT435



## RFID read/write head HF

DTRHF INRWIDUS03



## Application

Application	Detection of objects on transport equipment
Radio approval for	USA; Canada; EU/RED; Australia; Japan; China; Taiwan; India; Singapore; Ukraine
Note on radio approval	The list of countries applying the European Radio Equipment Directive 2014/53/EU (RED) can be found under “Downloads”.

## Electrical data

Operating voltage	[V]	19.2...28.8 DC; (Supply only via the DTE10x evaluation unit (to EN 60950-1))
Current consumption	[mA]	< 50
Protection class		III
Operating frequency	[MHz]	13,56
RFID standard		ISO 15693

## Monitoring range

Distance write/read head front	[mm]	160
Distance write/read head side	[mm]	120
Distance to the ID tag	[mm]	≤ 45

## Interfaces

Communication interface	DATA / DTE10x
-------------------------	---------------

## Operating conditions

Ambient temperature	[°C]	-20...60
Storage temperature	[°C]	-25...80
Protection		IP 67; IP 69K

## Tests / approvals

Shock resistance	EN 60068-2-27	50 g 11 ms / 40 g (6 ms, continuous)
Vibration resistance	EN 60068-2-6	20 g 10...2000 Hz

## Mechanical data

Weight	[g]	175.8
Housing		tubular

# ANT435



## RFID read/write head HF

DTRHF INRWIDUS03

Mounting	non-flush mountable
Dimensions [mm]	M30 x 1.5 / L = 70
Thread designation	M30 x 1.5
Material	housing: stainless steel; Protective cover: PPS

### Displays / operating elements

Display	Power	1 x LED, green
	tag communication	1 x LED, yellow

### Accessories


Items supplied	Nut 2 x M30 x 1,5
----------------	-------------------

### Remarks

Remarks	Singapore Not approved for operation, for export only.
Pack quantity	1 pcs.

### Electrical connection

Connector: 1 x M12; coding: A



### Connection

