


DX2045



Multifunction display for monitoring analog standard signals

DISPLAY/AX460/IO-Link/AC/DC



Product characteristics		
Communication interface		IO-Link
Dimensions	[mm]	48 x 112 x 116
Application		
Application		displaying and monitoring analog signals; e.g. pressure sensors, temperature sensors or flow sensors
Electrical data		
Frequency AC	[Hz]	50...60
Operating voltage	[V]	115...230 AC / 18...30 DC
Current consumption	[mA]	100
Power consumption	[W]	3
Inputs / outputs		
Number of inputs and outputs		Number of analog inputs: 2; Number of digital outputs: 4
Inputs		
Number of analog inputs		2; (Spannungs- oder Stromeingang)
Analog input (current)	[mA]	0...20
Analog input (voltage)	[V]	-10...10
Resolution of analog input		16 bit
Precision analog input	[%]	0,1
Outputs		
Number of digital outputs		4
Max. current load per output	[mA]	200
Overload protection		yes
Interfaces		
Communication interface		IO-Link
Transmission type		COM3 (230,4 kBaud)
IO-Link revision		1.1
Required master port class		A
Min. process cycle time	[ms]	3



Multifunction display for monitoring analog standard signals

DISPLAY/AX460/IO-Link/AC/DC

Operating conditions		
Ambient temperature	[°C]	-20...60
Storage temperature	[°C]	-25...70
Protection		IP 65
Protection rating terminals		IP 20
Tests / approvals		
EMC	EN 61000-6-2	
	EN 61000-6-3	
	EN 61000-6-4	
Mechanical data		
Weight	[g]	369
Type of mounting		panel cutout: 91 x 43 mm
Dimensions	[mm]	48 x 112 x 116
Material		Noryl UL94-V-0
Displays / operating elements		
Display	Color display	full graphic LCD display, Touch screen
Electrical connection		
screw terminals:		
Connection		

