E10378

Female cordset

ADOGH040MSN0020A04



Article no longer available - archive entry M12 x1

Application Ex zone 1 Electrical data Operating voltage [V] < 15 DC Operating conditions Ambient temperature [°C] -2590 Protection IP 67 Safety classification Max. internal capacitance [nF] 0.196 Max. internal inductance [µH] 4 Mechanical data Dimensions [mm] 15 x 15 x 43 Material TPU (urethane) blue Molded-body material TPU (urethane), blue Material nut brass, nickel-plated Remarks When using sockets in hazardous areas (ATEX)			
Electrical data Operating voltage [V] < 15 DC Operating conditions Ambient temperature [°C] -2590 Protection IP 67 Safety classification Max. internal capacitance [nF] 0.196 Max. internal inductance [µH] 4 Mechanical data Dimensions [mm] 15 x 15 x 43 Material TPU (urethane) blue Molded-body material TPU (urethane), blue Material nut brass, nickel-plated Remarks Remarks When using sockets in hazardous areas (ATEX)	Application		
Operating voltage [V] < 15 DC Operating conditions Ambient temperature [°C] -2590 Protection IP 67 Safety classification Max. internal capacitance [nF] 0.196 Max. internal inductance [μH] 4 Mechanical data Dimensions [mm] 15 x 15 x 43 Material TPU (urethane) blue Molded-body material TPU (urethane), blue Material nut brass, nickel-plated Remarks Remarks When using sockets in hazardous areas (ATEX)	Application		Ex zone 1
Operating conditions Ambient temperature [°C] -2590 Protection IP 67 Safety classification	Electrical data		
Ambient temperature [°C] -2590 Protection IP 67 Safety classification Max. internal capacitance [nF] 0.196 Max. internal inductance [µH] 4 Mechanical data Dimensions [mm] 15 x 15 x 43 Material TPU (urethane) blue Molded-body material TPU (urethane), blue Material nut brass, nickel-plated Remarks Remarks When using sockets in hazardous areas (ATEX)	Operating voltage	[V]	< 15 DC
Protection IP 67 Safety classification Max. internal capacitance [nF] 0.196 Max. internal inductance [μH] 4 Mechanical data Dimensions [mm] 15 x 15 x 43 Material TPU (urethane) blue Molded-body material TPU (urethane), blue Material nut brass, nickel-plated Remarks Remarks When using sockets in hazardous areas (ATEX)	Operating conditions		
Safety classification Max. internal capacitance [nF] 0.196 Max. internal inductance [µH] 4 Mechanical data Dimensions [mm] 15 x 15 x 43 Material TPU (urethane) blue Molded-body material TPU (urethane), blue Material nut brass, nickel-plated Remarks Remarks When using sockets in hazardous areas (ATEX)	Ambient temperature	[°C]	-2590
Max. internal capacitance [nF] 0.196 Max. internal inductance [μH] 4 Mechanical data Dimensions [mm] 15 x 15 x 43 Material TPU (urethane) blue Molded-body material TPU (urethane), blue Material nut brass, nickel-plated Remarks When using sockets in hazardous areas (ATEX)	Protection		IP 67
Max. internal inductance [μΗ] 4 Mechanical data Dimensions [mm] 15 x 15 x 43 Material TPU (urethane) blue Molded-body material TPU (urethane), blue Material nut brass, nickel-plated Remarks When using sockets in hazardous areas (ATEX)	Safety classification		
Mechanical data Dimensions [mm] 15 x 15 x 43 Material TPU (urethane) blue Molded-body material TPU (urethane), blue Material nut brass, nickel-plated Remarks Remarks When using sockets in hazardous areas (ATEX)	Max. internal capacitance	[nF]	0.196
Dimensions [mm] 15 x 15 x 43 Material TPU (urethane) blue Molded-body material TPU (urethane), blue Material nut brass, nickel-plated Remarks Remarks When using sockets in hazardous areas (ATEX)	Max. internal inductance	[μH]	4
Material TPU (urethane) blue Molded-body material TPU (urethane), blue Material nut brass, nickel-plated Remarks Remarks When using sockets in hazardous areas (ATEX)	Mechanical data		
Molded-body material Material nut TPU (urethane), blue brass, nickel-plated Remarks When using sockets in hazardous areas (ATEX)	Dimensions	[mm]	15 x 15 x 43
Material nut brass, nickel-plated Remarks Remarks When using sockets in hazardous areas (ATEX)	Material		TPU (urethane) blue
Remarks When using sockets in hazardous areas (ATEX)	Molded-body material		TPU (urethane), blue
Remarks When using sockets in hazardous areas (ATEX)	Material nut		brass, nickel-plated
	Remarks		
there are special requirements regarding withing.	Remarks		When using sockets in hazardous areas (ATEX) there are special requirements regarding wiring.
The requirements of the applicable installation regulations must be absolutely adhered to by the user on his own responsibility.			
Pack quantity 1 pcs.	Pack quantity		1 non

E10378

Female cordset

ADOGH040MSN0020A04



Electrical connection

Cable: 20 m, PUR / PVC, blue, Ø 5 mm; $4 \times 0.34 \text{ mm}^2$ ($42 \times Ø 0.1 \text{ mm}$)

Electrical connection - Socket

Connector: $1 \times M12$, straight; coding: A; Moulded body: TPU (urethane), blue; Locking: brass, nickel-plated; Tightening torque: $0.5 \times M12$, straight; coding: A; Moulded body: TPU (urethane), blue; Locking: brass, nickel-plated; Tightening torque: $0.5 \times M12$, straight; coding: A; Moulded body: TPU (urethane), blue; Locking: brass, nickel-plated; Tightening torque: $0.5 \times M12$, straight; coding: A; Moulded body: TPU (urethane), blue; Locking: brass, nickel-plated; Tightening torque: $0.5 \times M12$, straight; coding: $0.5 \times$



Connection

Core colors:

 BK =
 black

 BN =
 brown

 BU =
 blue

 WH =
 white