




Inductive sensor

IIB2012BAROG/UP/Sonderstecker

Article no longer available - archive entry



1 LED 2 x

Product characteristics

Electrical design	PNP/NPN
Output function	normally open
Sensing range [mm]	12
Housing	Threaded type
Dimensions [mm]	M30 x 1.5 / L = 44

Application

System	Increased sensing range; optical setting aid
--------	--

Electrical data

Operating voltage [V]	10...36 DC
Protection class	II
Reverse polarity protection	no

Outputs

Electrical design	PNP/NPN
Output function	normally open
Max. voltage drop switching output DC [V]	5
Minimum load current [mA]	5
Max. leakage current [mA]	1
Permanent current rating of switching output DC [mA]	100
Switching frequency DC [Hz]	100
Short-circuit protection	no
Overload protection	no

Monitoring range

Sensing range [mm]	12
Operating distance [mm]	0...9.7
Increased sensing range	yes

Accuracy / deviations

Correction factor	steel: 1 / stainless steel: 0.7 / brass: 0.4 / aluminum: 0.3 / copper: 0.2
-------------------	--

II5777



Inductive sensor

IIB2012BAROG/UP/Sonderstecker

Hysteresis	[% of Sr]	1...15
------------	-----------	--------

Operating conditions

Ambient temperature	[°C]	-25...70
---------------------	------	----------

Protection	IP 67
------------	-------

Tests / approvals

EMC	EN 60947-5-2	
	EN 55011	class B

Mechanical data

Weight	[g]	164.525
--------	-----	---------

Housing	Threaded type
---------	---------------

Mounting	flush mountable
----------	-----------------

Dimensions	[mm]	M30 x 1.5 / L = 44
------------	------	--------------------

Thread designation	M30 x 1.5
--------------------	-----------

Material	brass white bronze coated; PBT
----------	--------------------------------

Displays / operating elements

Display	Switching status	1 x LED, red
	Switching status	1 x LED, green

Optical setting aid	yes
---------------------	-----

Accessories

Items supplied	lock nuts: 2
----------------	--------------

Remarks

Pack quantity	1 pcs.
---------------	--------

Electrical connection - plug

Cable: 0.5 m, PUR / PVC

Connector: 1 x M12; coding: A



II5777



Inductive sensor

IIB2012BAROG/UP/Sonderstecker

Connection

