

## OWS-00KG/AS

Alternative articles: OJ5008

Technical drawing of the LED module showing front and side views with dimensions.

**Front View Dimensions:**

- Total width: 74
- Distance from mounting hole to center of LED array: 60
- Distance from mounting hole to first LED: 15
- Distance between LEDs: 3,2
- Distance from center of LED array to mounting hole: 5,5
- Distance from center of LED array to mounting hole (bottom): 4,2
- Distance from center of LED array to mounting hole (bottom): 9
- Distance from center of LED array to mounting hole (bottom): 28
- Distance from center of LED array to mounting hole (bottom): 36
- Distance from center of LED array to mounting hole (bottom): 24
- Distance from center of LED array to mounting hole (bottom): 16
- Mounting hole: M8x1
- LED array: 3 LED

**Side View Dimensions:**

- Height: 10
- Width: 4
- Width: 20

# OW1010




## Through-beam sensor transmitter

OWS-00KG/AS

Mechanical data		
Housing		rectangular
Dimensions	[mm]	36 x 60 x 10
Material		ABS reinforced glass-fiber
Lens material		PMMA
Displays / operating elements		
Display	Power	1 x LED, green
Remarks		
Pack quantity		1 pcs.

### Electrical connection

Connector: 1 x M8; coding: A



### Connection

