

PN7692



Pressure sensor with display

PN-100-SEN14-QFRKG/US/ IV



- 1 alphanumeric display 4-digit red/green
- 2 LEDs Display unit / Switching status
- 3 Programming button
- 4 upper part of the housing can be rotated 345°



Product characteristics

| | | | |
|------------------------------|--|--------------|------------|
| Number of inputs and outputs | Number of digital outputs: 2 | | |
| Measuring range | 0...100 bar | 0...1450 psi | 0...10 MPa |
| Process connection | threaded connection 1/4" NPT external thread | | |

Application

| | | | |
|--|--|----------|--------|
| Special feature | gold-plated contacts | | |
| Measuring element | ceramic-capacitive pressure measuring cell | | |
| Application | for industrial applications | | |
| Media | Liquids | | |
| Conditionally suitable for | use in gases at pressures > 25 bar only on request | | |
| Medium temperature [°C] | -25...80 | | |
| Min. burst pressure | 650 bar | 9400 psi | 65 MPa |
| Pressure rating | 300 bar | 4350 psi | 30 MPa |
| Type of pressure | relative pressure | | |
| MAWP (for applications according to CRN) [bar] | 125 | | |

Electrical data

| | | | |
|---------------------------------|----------------------------|--|--|
| Operating voltage [V] | 18...30 DC; (to SELV/PELV) | | |
| Current consumption [mA] | < 35 | | |
| Min. insulation resistance [MΩ] | 100; (500 V DC) | | |
| Protection class | III | | |

PN7692



Pressure sensor with display

PN-100-SEN14-QFRKG/US/ IV

| | |
|-----------------------------|-----|
| Reverse polarity protection | yes |
| Power-on delay time [s] | 0.3 |
| Integrated watchdog | yes |

Inputs / outputs

| | |
|------------------------------|------------------------------|
| Number of inputs and outputs | Number of digital outputs: 2 |
|------------------------------|------------------------------|

Outputs

| | |
|--|---|
| Total number of outputs | 2 |
| Output signal | switching signal; IO-Link; (configurable) |
| Electrical design | PNP/NPN |
| Number of digital outputs | 2 |
| Output function | normally open / closed; (configurable) |
| Max. voltage drop switching output DC [V] | 2.5 |
| Permanent current rating of switching output DC [mA] | 150; (200 (...60 °C) 250 (...40 °C)) |
| Switching frequency DC [Hz] | < 170 |
| Short-circuit protection | yes |
| Type of short-circuit protection | yes (non-latching) |
| Overload protection | yes |

Measuring/setting range

| | | | |
|-----------------|-------------|--------------|------------|
| Measuring range | 0...100 bar | 0...1450 psi | 0...10 MPa |
|-----------------|-------------|--------------|------------|

Factory setting / CMPT = 2

| | | | |
|-----------------------------------|----------------|---------------|-----------------|
| Set point SP | 1...100 bar | 10...1450 psi | 0.1...10 MPa |
| Reset point rP | 0.5...99.5 bar | 5...1445 psi | 0.05...9.95 MPa |
| Min. difference between SP and rP | 0.5 bar | 10 psi | 0.05 MPa |
| In steps of | 0.5 bar | 5 psi | 0.05 MPa |

Status_B High Resolution / CMPT = 3

| | | | |
|-----------------------------------|----------------|---------------|-----------------|
| Set point SP | 0.8...100 bar | 12...1450 psi | 0.08...10 MPa |
| Reset point rP | 0.3...99.5 bar | 5...1443 psi | 0.03...9.95 MPa |
| Min. difference between SP and rP | 0.5 bar | 8 psi | 0.05 MPa |
| In steps of | 0.1 bar | 1 psi | 0.01 MPa |

Accuracy / deviations

| | |
|---|---|
| Switch point accuracy [% of the span] | < ± 0,5 |
| Repeatability [% of the span] | < ± 0,1; (with temperature fluctuations < 10 K) |
| Characteristics deviation [% of the span] | < ± 0,25 (BFSL) / < ± 0,5 (LS); (BFSL = Best Fit Straight Line; LS = limit value setting) |
| Hysteresis deviation [% of the span] | < ± 0,25 |
| Long-term stability [% of the span] | < ± 0,05; (per 6 months) |
| Temperature coefficient zero point [% of the span / 10 K] | < ± 0,2; (-0...80 °C) |

PN7692



Pressure sensor with display

PN-100-SEN14-QFRKG/US/ IV

| Temperature coefficient span [% of the span / 10 K] | < ± 0,2; (-0...80 °C) | | | | | | | | | |
|--|--|------------------------------|------------|----------------------------|-----|-------------------------------------|-----|------------------------------|---|--|
| Reaction times | | | | | | | | | | |
| Response time [ms] | < 3 | | | | | | | | | |
| Delay time programmable dS, dr [s] | 0...50 | | | | | | | | | |
| Software / programming | | | | | | | | | | |
| Parameter setting options | hysteresis / window; normally open / closed; switching logic; switch-on/switch-off delay; Damping; Display unit | | | | | | | | | |
| Interfaces | | | | | | | | | | |
| Communication interface | IO-Link | | | | | | | | | |
| Transmission type | COM2 (38,4 kBaud) | | | | | | | | | |
| IO-Link revision | 1.1 | | | | | | | | | |
| SDCI standard | IEC 61131-9 | | | | | | | | | |
| SIO mode | yes | | | | | | | | | |
| Required master port class | A; (when pin 2 not connected: B) | | | | | | | | | |
| Supported DeviceIDs | <table border="1"> <thead> <tr> <th>Type of operation</th> <th>DeviceID</th> </tr> </thead> <tbody> <tr> <td>Factory setting / CMPT = 2</td> <td>452</td> </tr> <tr> <td>Status_B High Resolution / CMPT = 3</td> <td>629</td> </tr> </tbody> </table> | Type of operation | DeviceID | Factory setting / CMPT = 2 | 452 | Status_B High Resolution / CMPT = 3 | 629 | | | |
| Type of operation | DeviceID | | | | | | | | | |
| Factory setting / CMPT = 2 | 452 | | | | | | | | | |
| Status_B High Resolution / CMPT = 3 | 629 | | | | | | | | | |
| Note | For further information please see the IODD PDF file at "Downloads" | | | | | | | | | |
| Factory setting / CMPT = 2 | | | | | | | | | | |
| Profiles | Smart Sensor - SSP 0 | Generic Profiled Sensor | | | | | | | | |
| | Function | Device identification | | | | | | | | |
| | Function | Process data variable | | | | | | | | |
| | Function | Device diagnosis | | | | | | | | |
| Min. process cycle time [ms] | 2.3 | | | | | | | | | |
| IO-Link resolution pressure | 0.1 bar | 0.01 MPa | | | | | | | | |
| IO-Link process data (cyclical) | <table border="1"> <thead> <tr> <th>Function</th> <th>bit length</th> </tr> </thead> <tbody> <tr> <td>pressure</td> <td>14</td> </tr> <tr> <td>binary switching information</td> <td>2</td> </tr> </tbody> </table> | Function | bit length | pressure | 14 | binary switching information | 2 | | | |
| Function | bit length | | | | | | | | | |
| pressure | 14 | | | | | | | | | |
| binary switching information | 2 | | | | | | | | | |
| IO-Link functions (acyclical) | application specific tag | | | | | | | | | |
| Status_B High Resolution / CMPT = 3 | | | | | | | | | | |
| Profiles | Smart Sensor - SSP 3.1 | Measuring Sensor | | | | | | | | |
| | Common - I&D | Identification and Diagnosis | | | | | | | | |
| Min. process cycle time [ms] | 3 | | | | | | | | | |
| IO-Link resolution pressure | 0.05 bar | 0.005 MPa | | | | | | | | |
| IO-Link process data (cyclical) | <table border="1"> <thead> <tr> <th>Function</th> <th>bit length</th> </tr> </thead> <tbody> <tr> <td>pressure</td> <td>16</td> </tr> <tr> <td>device status</td> <td>4</td> </tr> <tr> <td>binary switching information</td> <td>2</td> </tr> </tbody> </table> | Function | bit length | pressure | 16 | device status | 4 | binary switching information | 2 | |
| Function | bit length | | | | | | | | | |
| pressure | 16 | | | | | | | | | |
| device status | 4 | | | | | | | | | |
| binary switching information | 2 | | | | | | | | | |
| IO-Link functions (acyclical) | application specific tag | | | | | | | | | |
| Operating conditions | | | | | | | | | | |
| Ambient temperature [°C] | -25...80 | | | | | | | | | |
| Storage temperature [°C] | -40...100 | | | | | | | | | |
| Protection | IP 65; IP 67 | | | | | | | | | |

PN7692



Pressure sensor with display

PN-100-SEN14-QFRKG/US/ IV

| Tests / approvals | | |
|--|---|---|
| EMC | DIN EN 61000-6-2 | |
| | DIN EN 61000-6-3 | |
| Shock resistance | DIN EN 60068-2-27 | 50 g (11 ms) |
| Vibration resistance | DIN EN 60068-2-6 | 20 g (10...2000 Hz) |
| MTTF [years] | | 286 |
| UL approval | UL approval number | J002 |
| Pressure equipment directive | sound engineering practice; can be used for group 2 fluids; group 1 fluids on request | |
| Mechanical data | | |
| Weight [g] | | 282 |
| Housing | | tubular |
| Dimensions [mm] | | Ø 34 / L = 90.7 |
| Material | stainless steel (1.4404 / 316L); PBT+PC-GF30; PBT-GF20; PC | |
| Materials (wetted parts) | stainless steel (1.4404 / 316L); ceramics; FKM | |
| Min. pressure cycles | | 100 million |
| Tightening torque [Nm] | 2...3 turns after hand-fastening; recommended tightening torque; Depends on lubrication, seal and pressure rating | |
| Process connection | threaded connection 1/4" NPT external thread | |
| Restrictor element integrated | no (can be retrofitted) | |
| Displays / operating elements | | |
| Display | Display unit | 3 x LED, green (bar, psi, MPa) |
| | Switching status | 2 x LED, yellow |
| | Measured values | alphanumeric display, red/green 4-digit |
| Remarks | | |
| Pack quantity | | 1 pcs. |
| Electrical connection | | |
| Connector: 1 x M12; coding: A; Contacts: gold-plated | | |
| | | |

PN7692



Pressure sensor with display

PN-100-SEN14-QFRKG/US/ IV

Connection



| | |
|------|---|
| OUT1 | Switching output IO-Link |
| OUT2 | Switching output Colors to DIN EN 60947-5-2 Core colors : |
| BK = | black |
| BN = | brown |
| BU = | blue |
| WH = | white |