


SBG432



Flow transmitters with fast response time

SBG12HF010KG/US

Please note the changed housing design!



1 socket head screw



Product characteristics		
Measuring range	[l/min]	0.3...15
Process connection		threaded connection G 1/2
Application		
Media		Liquids; water; glycol solutions; Coolants
Medium temperature	[°C]	-10...100
Pressure rating	[bar]	40
Pressure rating	[MPa]	4
Electrical data		
Operating voltage	[V]	18...32 DC; (to SELV/PELV)
Current consumption	[mA]	< 35



Flow transmitters with fast response time

SBG12HF010KG/US

Protection class	III
Reverse polarity protection	yes
Outputs	
Output signal	analog signal
Analog current output [mA]	4...20
Max. load [Ω]	500
Short-circuit protection	yes
Overload protection	yes
Measuring/setting range	
Measuring range [l/min]	0.3...15
Accuracy / deviations	
Repeatability [% of the final value]	1
Measuring error [% of the final value]	± 5
Reaction times	
Response time [s]	< 0.01
Operating conditions	
Ambient temperature [°C]	0...60
Storage temperature [°C]	-15...80
Protection	IP 65; IP 67
Tests / approvals	
EMC	DIN EN 61000-6-2
	DIN EN 61000-6-3
Shock resistance	DIN EN 60068-2-27
Vibration resistance	DIN EN 60068-2-6
MTTF [years]	778
Mechanical data	
Weight [g]	548.5
Material	brass chemically nickel-plated; PP; stainless steel (1.4404 / 316L); aluminum anodized; PA
Materials (wetted parts)	stainless steel (1.4401 / 316); brass; brass chemically nickel-plated; PP; PPS; O-ring: FKM
Process connection	threaded connection G 1/2
Switching cycles mechanical	10 million
Remarks	
Remarks	Recommendation Use 200 micron filtration
	All data refer to water (20 °C).
Notes	Please note the changed housing design!
Pack quantity	1 pcs.

SBG432



Flow transmitters with fast response time


SBG12HF010KG/US

Electrical connection

Connector: 1 x M12; coding: A




Connection



Diagrams and graphs

Pressure loss



dP Pressure loss
Q volumetric flow quantity